

Item #:	178Z1R2EWMS		Project:	
Otv:		Date:		Approval:

Avantco Z1-R2-EWMS 29" VersaHub WiFi-Enabled Right-Hinged Solid Half Door Stainless Steel Reach-In Refrigerator with 2 Drawers

Item#178Z1R2EWMS







Technical Data

29 Inches
32 3/16 Inches
81 11/16 Inches
24 3/8 Inches
27 1/8 Inches
56 11/16 Inches
2.6 Amps
60 Hz
1 Phase
115 Volts


Features

- VersaHub platform monitors unit failure, open doors, and temperature via text/email notifications
- Corrosion-resistant stainless steel interior and exterior
- Full-size food pan slides hold 33% more weight than standard shelf clips
- Rear air duct for exceptional circulation
- R-290 refrigerant; 115V; 1/3 hp
- Note: only the refrigerator holds the ETL certification

Certifications



ETL Sanitation





Energy Star Qualified



Technical Data

Wattage	264 Watts	
vvattage		
Access Type	Doors Drawers	
Capacity	21.68 cu. ft.	
Capacity (per Shelf)	120 lb.	
Casters	With Casters	
Color	Silver	
Compressor Location	Top Mounted	
Construction	All Stainless Steel	
Door Type	Solid	
Dutch Half Doors	With Dutch Half Doors	
Features	Automatic Electric Defrost Digital Display Electronic Controller Energy Star Qualified Removable Magnetic Door Gaskets Removable Magnetic Drawer Gaskets Self-Closing Doors VersaHub Compatible WiFi Enabled	
Hinge Location	Right	
Horsepower	1/3 hp	
Installation Type	Freestanding	
Number of Compressors	1 Compressor	
Number of Doors	1 Doors	
Number of Drawers	2 Drawers	
Number of Shelves	2 Shelves	
Number of Tray Slides	2	
Plug Type	NEMA 5-15P	
Refrigerant Type	R-290	
Sections	1 Section	
Starting Amps	7.9 Amps	
Starting Wattage	792 Watts	
Starting Wattage Temperature Range	792 Watts 33 - 40 Degrees F	



Notes & Details

Your establishment relies on refrigeration for proper food safety, and with this Avantco Z1-R2-EWMS 29" VersaHub WiFi-Enabled right-hinged solid half door stainless steel reach-in refrigerator with 2 drawers, you receive performance you can depend on! A corrosion-resistant, all-stainless steel interior and exterior construction provides increased durability and a sleek appearance. This model uses the VersaHub platform to provide live notifications, history, and other WiFi-enabled updates. The one self-closing and stay-open locking solid door gives your staff the ability to more quickly and easily load your refrigerator when you get a delivery, while the drawers offer easy inventory access. Plus, a door open alarm alerts users to when the doors have been open for too long to keep your inventory safe and fresh.

This model features 2 plastic-coated steel shelves that fit in the refrigerator's pan slides. These slides fit full-size food pans (sold separately) and hold 33% more weight than shelf clips to make loading and unloading a breeze! The full-length U-shaped door handle further expedites the loading process. Since this model has a half door, you're able to keep other food cold if you're only opening half of the refrigerated space at a time. Thanks to the rear air duct, this model has exceptional air circulation. Included casters allow users to easily move and clean under the unit.

Designed to maintain temperatures from 33-40 degrees Fahrenheit, this refrigerator boasts a top-mounted 1/3 hp compressor that uses R-290 refrigerant. This specialized refrigerant has an ozone depletion potential (ODP) of 0 and a global warming potential (GWP) of 3. In addition, the top-mounted compressor is further from the floor than on a bottom-mounted unit; meaning it'll get less dirty and won't be accidentally kicked. For optimal temperature retention, the entire cabinet is foamed-in place using polyurethane insulation. Other helpful features include the state-of-the-art Carel iJ controller, automatic defrosting, and digital temperature control with digital display. This item requires a 115V electrical connection for operation.

MARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.