

Item #: 178Z1RN Project: _____

Qty: _____ Date: _____ Approval: _____

Avantco Z-1R-N 17 11/16" Stainless Steel Solid Door Narrow Reach-In Refrigerator

Item #178Z1RN



Technical Data

Width	17 11/16 Inches
Depth	31 15/16 Inches
Height	81 5/8 Inches
Interior Width	13 15/16 Inches
Interior Depth	24 7/16 Inches
Interior Height	61 Inches
Amps	1.9 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	115 Volts

Features

- Corrosion-resistant stainless steel interior and exterior
- Self-closing and stay-open locking solid door
- Interior features full-size food pan slides and a perforated rear plenum
- Cabinet and maintenance alarms will sound and display on Carel iJ controller
- Top-mounted 1/4 hp compressor uses R-290 refrigerant

Certifications



ETL Listed



5-15P

Technical Data

Access Type	Doors
Capacity	10.59 cu. ft.
Casters	With Casters
Color	Silver
Compressor Location	Top Mounted
Construction	All Stainless Steel
Door Style	Swing
Door Type	Solid
Dutch Half Doors	Without Dutch Half Doors
Features	Automatic Electric Defrost Corrosion-Resistant Digital Display Digital Temperature Controller Locking Doors Narrow Body Self-Closing Doors Stay-Open Doors
Hinge Location	Right
Horsepower	1/4 hp
Installation Type	Freestanding
Number of Doors	1 Doors
Number of Shelves	3 Shelves
Plug Type	NEMA 5-15P
Refrigerant Type	R-290
Sections	1 Section
Temperature Range	33 - 40 Degrees F
Type	Refrigerators

Notes & Details

Receive performance you can depend on with this Avantco 17 11/16" stainless steel solid door narrow reach-in refrigerator! Your establishment relies on refrigeration for proper food safety, whether you're storing milk, eggs, vegetables, or freshly made foods. With this reach-in refrigerator, your ingredients and fully prepared foods will stay at safe refrigerated temperatures. For optimal temperature retention, the entire cabinet is foamed-in-place using polyurethane insulation. Other helpful features include the state-of-the-art Carel iJ controller and automatic defrosting.

A corrosion-resistant stainless steel interior and exterior construction provides increased durability, keeps out moisture, and resists rust. The perforated rear plenum ensures evenly distributed airflow throughout, allowing you to load the unit with bulky items without impeding circulation. Digital temperature control allows you to easily adjust the temperature of your refrigerator's cabinet. Plus, the automatic defrost function keeps food fresh and properly chilled! The controller's audible alarms alert you to temperatures too high or too low, extended door opening, and the need to clean the unit's condenser.

This Avantco refrigerator features one solid door that offers a sleek appearance and keeps your inventory protected thanks to its ability to lock. The self-closing and stay-open solid door allows users to load the refrigerator quickly and easily after a delivery, while full-length U-shaped door handle further expedites the loading process. This unit features 3 plastic-coated steel shelves that fit in the refrigerator's versatile shelf-rail design. These slides support 33% more weight than shelf clips and can be used to hold full-size food pans (sold separately).

Designed to maintain temperatures from 33 to 40 degrees Fahrenheit, this refrigerator boasts a top-mounted 1/4 hp compressor that uses R-290 refrigerant. In addition, the top-mounted compressor is further from the floor than on a bottom-mounted unit, meaning it'll get less dirty and won't be accidentally kicked. It requires a 115V electrical connection for operation.

⚠ WARNING: This product can expose you to chemicals including di(2-ethylhexyl)phthalate (DEHP), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.