



MAX-LIFT Scissor Lift Tables

The MAX-LIFT is the best value in lift tables with unparalleled features! It reduces awkward bending and lifting, since the workload is always at the correct level. The possibility of back injuries is reduced and productivity is increased

The Max-Lift table line offers the following standard features:

- Trapped top and bottom scissor arms
- Built-in safety bars
- Grease fittings on pivot points and cam rollers
- Magnetic backed control box
- High quality fit and finish



**Magnetic
Backed Hand
Control-
Standard**



**Optional Foot
Control**

**Zerk Fittings on
Camrollers and
Pivot Points**

**Integral, retractable
maintenance safety bars**

**All welded construction
meets AWS standard service**

**Tables conform to or exceed
ANSI MH 29.1-1994/2008**



**Captured 'Lift-Lok'
secures top and
base leg rollers**



**High Quality Camrollers,
Pivot Pins and Bearings**



**Motor &
Controls
are easily
accessible**



MAX-LIFT Scissor Lift Tables

MODEL	CAPACITY	STATIC EDGE LOAD	ROLLING EDGE LOAD	BASE FRAME	PLATFORM	LOWERED HEIGHT	RAISED HEIGHT	HAND/FOOT CONTROL
BM-MS-2K-43R-2448-H	2000	2000	1500	24" X 48"	24" X 48"	7.5"	43"	HAND
BM-MS-2K-43R-2448-F	2000	2000	1500	24" X 48"	24" X 48"	7.5"	43"	FOOT
BM-MS-2K-43R-3648-H	2000	2000	1500	24" X 48"	36" X 48"	7.5"	43"	HAND
BM-MS-2K-43R-3648-F	2000	2000	1500	24" X 48"	36" X 48"	7.5"	43"	FOOT
BM-MS-2K-43R-3660-H	2000	2000	1500	24" X 48"	36" X 60"	7.5"	43"	HAND
BM-MS-2K-43R-3660-F	2000	2000	1500	24" X 48"	36" X 60"	7.5"	43"	FOOT
BM-MS-2K-43R-3672-H	2000	2000	1500	24" X 48"	36" X 72"	7.5"	43"	HAND
BM-MS-2K-43R-3672-F	2000	2000	1500	24" X 48"	36" X 72"	7.5"	43"	FOOT
BM-MS-2K-43R-4848-H	2000	2000	1500	24" X 48"	48" X 48"	7.5"	43"	HAND
BM-MS-2K-43R-4848-F	2000	2000	1500	24" X 48"	48" X 48"	7.5"	43"	FOOT
BM-MS-2K-43R-4872-H	2000	2000	1500	24" X 48"	48" X 72"	7.5"	43"	HAND
BM-MS-2K-43R-4872-F	2000	2000	1500	24" X 48"	48" X 72"	7.5"	43"	FOOT
BM-MS-4K-43R-2448-H	4000	3000	2000	24" X 48"	24" X 48"	7.5"	43"	HAND
BM-MS-4K-43R-2448-F	4000	3000	2000	24" X 48"	24" X 48"	7.5"	43"	FOOT
BM-MS-4K-43R-3648-H	4000	3000	2000	24" X 48"	36" X 48"	7.5"	43"	HAND
BM-MS-4K-43R-3648-F	4000	3000	2000	24" X 48"	36" X 48"	7.5"	43"	FOOT
BM-MS-4K-43R-3660-H	4000	3000	2000	24" X 48"	36" X 60"	7.5"	43"	HAND
BM-MS-4K-43R-3660-F	4000	3000	2000	24" X 48"	36" X 60"	7.5"	43"	FOOT
BM-MS-4K-43R-3672-H	4000	3000	2000	24" X 48"	36" X 72"	7.5"	43"	HAND
BM-MS-4K-43R-3672-F	4000	3000	2000	24" X 48"	36" X 72"	7.5"	43"	FOOT
BM-MS-4K-43R-4848-H	4000	3000	2000	24" X 48"	48" X 48"	7.5"	43"	HAND
BM-MS-4K-43R-4848-F	4000	3000	2000	24" X 48"	48" X 48"	7.5"	43"	FOOT
BM-MS-4K-43R-4872-H	4000	3000	2000	24" X 48"	48" X 72"	7.5"	43"	HAND
BM-MS-4K-43R-4872-F	4000	3000	2000	24" X 48"	48" X 72"	7.5"	43"	FOOT
BM-MS-6K-43R-4848-H	6000	3500	2350	24" X 48"	48" X 48"	7.5"	43"	HAND
BM-MS-6K-43R-4848-F	6000	3500	2350	24" X 48"	48" X 48"	7.5"	43"	FOOT
BM-MS-2K-55R-2564-H	2000	2000	1500	25" X 64"	25" X 64"	7.63"	55"	HAND
BM-MS-2K-55R-2564-F	2000	2000	1500	25" X 64"	25" X 64"	7.63"	55"	FOOT
BM-MS-2K-55R-4864-H	2000	2000	1500	25" X 64"	48" X 64"	7.63"	55"	HAND
BM-MS-2K-55R-4864-F	2000	2000	1500	25" X 64"	48" X 64"	7.63"	55"	FOOT
BM-MS-2K-55R-4896-H	2000	2000	1500	25" X 64"	48" X 96"	7.63"	55"	HAND
BM-MS-2K-55R-4896-F	2000	2000	1500	25" X 64"	48" X 96"	7.63"	55"	FOOT
BM-MS-4K-55R-2564-H	4000	3000	2000	25" X 64"	25" X 64"	7.63"	55"	HAND
BM-MS-4K-55R-2564-F	4000	3000	2000	25" X 64"	25" X 64"	7.63"	55"	FOOT
BM-MS-4K-55R-4864-H	4000	3000	2000	25" X 64"	48" X 64"	7.63"	55"	HAND
BM-MS-4K-55R-4864-F	4000	3000	2000	25" X 64"	48" X 64"	7.63"	55"	FOOT
BM-MS-4K-55R-4896-H	4000	3000	2000	25" X 64"	48" X 96"	7.63"	55"	HAND
BM-MS-4K-55R-4896-F	4000	3000	2000	25" X 64"	48" X 96"	7.63"	55"	FOOT

- Internally mounted 1-1/2 HP, 115/230V-I-60 or 230/460-3-60 intermittent duty TENV super torque motor
- Specify voltage
- 115V operating control voltage
- NEMA constant pressure
- Magnet-backed up/down push button control station with 10 ft. straight or coiled cord
- NEMA-I prewired controls and electrical connectors
- Control box contains contactor, control transformer, thermal overload and fuse
- All controller components meet UL and/or CSA specifications
- Cylinders with internal stops
- 10 ft. power cord (connector not included)
- Hard, chrome-plated, polished shafting hydraulic cylinder piston rods
- Surfaces degreased, descaled and finished with safety yellow

- and blue enamel
- Smooth steel top with yellow and black safety stripes
- S.A.E. hoses and fittings
- Integral safety restraint maintenance bars
- Internal gear pump with check valve, relief valve, solenoid valve
- Includes hydraulic oil and filter

Limited Warranty

- 90-day repair or replacement on total product.
- 90-day on electrical components, except motors
- 5 years or 100,000 cycles on bearing
- 5 years on structural components

Options:

- Foot control switch with 10 ft. cord
- Accordion skirting or roller curtain skirting
- Tapered top guards for pit mounting
- Rotating top
- Casters
- Semi-live with jack handle
- Special controls
- All stainless steel top
- Perimeter safety bar
- Other options available
- Contact factory for special requirements

Specifications are subject to change without notice. Consult your dealer for current information. Lift Products, Inc. products are covered by patents pending and other rights reserved.

Call 800-762-8327 or visit Ballymore.com for more information or a FAST quote.