

STANDARD ROLLING LADDERS WITH SPRING LOADED CASTERS

- 450 lb. capacity • Working heights up to 12'
- Spring loaded swivel casters retract under user's weight
- 7" deep steps with 10" deep top step on 1 - 4 step models shown with (*) in the chart below
- 14" deep top step on 4 - 7 step FSH models
- **Specify tread type when ordering**
- 1 - 4 step ladders (*) ship unassembled in a box, and are eligible for UPS shipping
- 4 - 7 step FSH models ship unassembled
- Specify set-up (SU) if required***
- Available in all welded construction
- Gray powder coat finish
- Complies with applicable OSHA & ANSI standards
- CAL OSHA available



FSH526X

STEPS INCLUDING TOP STEP	HEIGHT INCHES		16" WIDE STEP			24" WIDE STEP		
	TOP STEP	OVER ALL	MODEL #	BASE W" x L"	WGT Lbs.	MODEL #	BASE W" x L"	WGT Lbs.
NO HANDRAILS								
1 STEP	12	12	118*	18 x 16	18	126*	26 x 16	20
2 STEP	19	19	218*	20 x 19	22	226*	30 x 19	28
3 STEP	28.5	28.5	318*	20 x 25	31	326*	30 x 25	36
4 STEP	38	38	418*	20 x 31	42	426*	30 x 31	51
WITH HANDRAILS								
2 STEP	19	49	*H218*	20 x 19	36	*H226*	30 x 19	42
3 STEP	28.5	58.5	*H318*	20 x 25	45	*H326*	30 x 25	50
4 STEP	38	68	*H418*	20 x 31	56	*H426*	30 x 31	65
4 STEP	40	73	FSH418	20 x 35	68	FSH426	30 x 35	80
5 STEP	50	83	FSH518	20 x 42	75	FSH526	30 x 42	87
6 STEP	60	93	FSH618	24 x 49	83	FSH626	30 x 49	98
7 STEP	70	103	FSH718	24 x 56	89	FSH726	30 x 56	108

*Eligible for UPS ♦ Handrails may ship in separate box



Number Of Steps	Top Step Depth	Top Step Height	Bottom W x D	MODEL #
Aluminum				
2	14"	20"	20" x 23"	WLAR002166
2	14"	20"	29" x 23"	WLAR002246
3	14"	30"	22" x 31"	WLAR003166
3	14"	30"	29" x 31"	WLAR003246
2	21"	20"	20" x 30"	WLAR002166-D4
2	21"	20"	29" x 30"	WLAR002246-D4
2	21"	20"	29" x 30"	WLAR002246-D4
2	28"	20"	20" x 37"	WLAR002166-D5
2	28"	20"	29" x 37"	WLAR002246-D5
Steel				
3	30"	10"	30" x 28"	WLSR003246

NOTE: Models Shown are for Perforated Treads
Specify Tread Type when ordering

MOBILE STEP STOOLS

- **450 rated capacity - Steel**
- Anti-Slip, Perforated or Grip Strut - Steel
- Powder-coated gray finish - Steel
- **350 rated capacity - Aluminum**
- Solid Ribbed, Perforated or Grip Strut Aluminum
- Standard mill finish - Aluminum
- Complies with applicable OSHA & ANSI standards

