

# Visit CO alarm

## BE1210



## Protect your home and family.

The CO alarm from Bellman & Symfon is part of the Visit smart home system that helps you to keep tabs on your home. The CO alarm discovers dangerous concentrations of carbon monoxide and relays the alarm directly to your Visit receiver – so you can get out of harm's way in time.

### How it works

If dangerous CO levels are detected, the CO alarm instantly activates your Visit receiver

that alerts you with sound, flashes and vibrations (depending on the receiver).

Knowing that you will get an early warning provides a peaceful night's sleep for both you and your family.

The Visit CO alarm uses advanced electrochemical sensor technology to detect carbon monoxide and is connected to the Visit system via a built-in Visit radio module.



### Features

**Secure detection**  
Electrochemical sensor

**Reliable radio link**  
Covers your entire home

**Long lasting power**  
Up to 5 years battery life

**Hush function**  
Silences the alarm temporarily

**Broadcast function**  
Relays alarms to the receivers






## Dimensions and weight

Height: 4.1", 105 mm  
Width: 4.7", 120 mm  
Depth: 1.6", 40 mm  
Weight: 6.5 oz, 185 g, incl. batteries



## Buttons and controls



## Features

- Sensor type  
Electrochemical sensor
- CO sensitivity  
Complies with UL2034. Certified to CSA Std. 6.19-01
- E.M. compatibility  
Complies with UL2034/FCC Part 15 and IC RSS-210
- Audible alarm  
Min. 85 dB(A) @ 10 ft (3 m)
- Radio connection  
Features a separate radio module inside the carbon monoxide alarm.
- Warns for low battery, fault and end-of-life
- Broadcast function  
Transmits the alarm to all other Visit receivers within range, overriding the radio key settings.
- Hush function  
Silences the horn for 4 minutes. At CO levels above 250 ppm the unit cannot be silenced.
- Activation
  - By the Test/Hush button  
(Checks electronics, sounder, sensor and current battery status)
  - By carbon monoxide
- Product lifetime  
10 years

## Power and battery

- Battery type  
2x Alkaline AAA type replaceable batteries
- Battery life  
Up to 5 years

## Environmental requirements

- For indoor use only
- Operating temperature  
32°F to 104°F (0°C to 40°C)
- Humidity range: 15% – 95% R.H. non-condensing

## Frequency and coverage

- Radio frequency: 433.92 MHz
- Coverage: 50–160m (55–175yd.), clear line of sight. The range is reduced by walls, large objects and other radio transmitters such as televisions and mobile phones.

## Regulatory requirements

- BE1220 complies with UL2034 / FCC Part 15 and IC RSS-210. Certified to CSA Std. 6.19-0.

## In the package

- BE1210 CO alarm
- Screws and plugs
- User manual



## CO alarm response

- The alarm is calibrated to respond to the following levels of carbon monoxide:

CO level	Alarm
> 45 ppm	On within 60 – 240 minutes
> 100 ppm	On within 10 – 50 minutes
> 250 ppm	On within 4 – 15 minutes
> 750 ppm	On within 3 minutes

## © and TM 2020, Bellman & Symfon AB

Bellman and Bellman & Symfon are registered trademarks owned by Bellman & Symfon AB, all rights reserved. All product designs are patented. This leaflet is subject to change without prior notice.

BE1210-433\_022DSH001

[bellman.com](http://bellman.com)