

| PROJECT: | | |
|----------|-------|------|
| ITEM# | | QTY: |
| MODEL# | | • |
| AIA # | SIS # | |
| APPROVED | I | |

BAR EQUIPMENT - COMPACTED

Model: BM23HC-S-31

BAR MOBILE / PORTABLE DRAFT BEER DISPENSER WITH DRAFT ARM





OPTIONS & ACCESSORIES

- Club models available
- · Custom tower hole location
- . Drip tray location change
- Wine models available
- Wine tap
- · Wine, beer & coffee faucet options
- 1-4 faucet
- 2, 3, or 4-way manifold
- Draft arm faucet lock (slide-on)

7 YEAR WARRANTY Parts, Labor, and Compressor

CABINET CONSTRUCTION

- Stainless steel exterior
- Interior construction utilizes galvanized steel on walls and ceiling, doorsill is stainless steel, reinforced floor made from heavy stainless steel
- Top is made from heavy-duty stainless steel including drip tray
- Mechanical control
- 3-in-1 Draft Solution uses a single stainless-steel tap to serve different beverages, such as wine, beer, and coffee (or other non-alcoholic beverages) through silver-lined, anti-microbial tubing that is 100% effective against the top 4 beverage spoiling bacteria
- . Tower has continuous source of cold air
- Three-inch (3") insulated tower with single faucet
- Beer waste bottle to capture beer from drain
- Self-closing door with lock, standard
- · Magnetic door gaskets for positive door sealing
- Field reversible door (hinge kit not included)
- Four-inch (4") heavy-duty casters
- · Certified for outdoor use
- Balanced, forced-air refrigeration system keeps beer in kegs ice cold for dispensing

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE & more
- Automatic, non-electric defrost
- Epoxy coated evaporator coil
- Maintains product temperatures between 36°F and 38°F




BEVERAGE-AIR.

Bar Equipment - Compacted Model: BM23HC-S-31


PLAN VIEW

- 24" OVERALL WIDTH -

ELEVATION VIEW



SIDE VIEW



| EXTERNAL DIMENSIONAL DATA | | | |
|-------------------------------|-------------------|--|--|
| Width Overall (in) | 24" | | |
| Depth Overall (in) | 30 3/8" | | |
| Height Overall (in) | 53 1/8" | | |
| Number of Doors | 1 | | |
| Depth with Door open 90° (in) | 51" | | |
| Door Openings (in) | 19 7/8" x 27 7/8" | | |
| INTERNAL DIMENSIONAL DATA | | | |
| NET Capacity (cubic ft). | 7.66 | | |
| Internal Width Useable (in) | 20" | | |
| Internal Depth Overall (in) | 22 1/4" | | |
| Internal Height Overall (in) | 29 5/8" | | |
| Number of 1/2 Kegs | 1 | | |

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

| ELECTRICAL DATA | | | |
|---------------------------|--------------------|--|--|
| Full Load Amps | 2.0 | | |
| Voltage | 115/60/1 | | |
| Nema Plug (8' cord) | 5-15P | | |
| REFRIGERATION DATA | | | |
| Horsepower | 1/6 | | |
| Capacity (BTU/Hr) | 1094 | | |
| Heat Rejection (BTU/Hr) | 1641 | | |
| Charge (lbs/grams/ounces) | 0.1213 / 55 / 1.94 | | |
| SHIPPING DATA | | | |
| Gross Weight - Crated | 180 lbs. | | |
| Height - Crated (in) | 43" | | |
| Width - Crated (in) | 27" | | |
| Depth - Crated (in) | 33" | | |

ELECTRICAL CONNECTION



115/60/1

Unit pre-wired at factory NEMA 5-15P and include 8' long cord and plug set.

3779 Champion Blvd., Winston-Salem, NC 27105 | 888-845-9800 | Fax: 336-245-6453 | Beverage-Air.com | Sales@bevair.com

Date Issued 8/25 | Printed in U.S.A.

