BOLTIC	S	B	0	LT		C
---------------	----------	---	---	----	--	---

Item #:	687BFM1510PC		Project:	
Otv:		Date		Approval:

Boltic 42" Powder Coat Air Curtain with Plunger Door Switch

Item#687BFM1510PC







Technical Data

Width	39 3/8 Inches
Depth	8 5/16 Inches
Height	10 1/4 Inches
Power Cord Length	59 Inches
Mounting Width	33 1/2 Inches
Hertz	60 Hz
Phase	1 Phase
Voltage	120 Volts
Wattage	400 Watts
Air Velocity	2559 - 3150 FPM

Features

- Retains internal room temperature when external door opens
- Prevents pests from coming inside
- Sleek powder coat construction
- 69-71 decibels for maintaining a low noise level
- Two different speeds

Certifications





(V) 5-15P (U) UL Listed, US



Technical Data

Airflow Rating	1354 - 1648 CFM
Color	White
Installation Type	Surface Mounted
Material	Powder Coated Metal
Noise Level	69 - 71 dB
Plug Type	NEMA 5-15P
Speeds	2 Speed
Style	Back Door Drive-Thru Window Front Door
Туре	Air Curtains

Notes & Details

Ensure your air temperature is controlled while keeping your entrance area free of pests with this Boltic 42" powder coat air curtain with plunger door switch! Whether your internal temperature needs to stay warm and heated or the AC needs to be kept inside, this air curtain is a great solution when entry points are exposed to the outdoor elements. Cutting down on the infiltration of outside air will save you money in climate-controlled areas. The blast of air has an air velocity of 2,559 to 3,150 FPM, making it an excellent repellent and helping to prevent unwanted pests from entering your establishment. It also maintains a low level of noise at only 69 to 71 decibels and will not disturb guests!

This air curtain is ideal for drive-thru windows, concession stands, building entrances, walk-in coolers, and patios. For added convenience, the plunger door switch automatically turns the fan on and off when the door opens and closes. The powder coating creates a hard finish, providing exceptional durability. The air curtain also features 2 different operating speeds to accommodate your needs. This unit requires a 120V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.