



PORTABLE FIRE EXTINGUISHERS

5.5 LB. Standard Stored Pressure Fire Extinguisher

DESCRIPTION

Buckeye's 5.5 lb. Standard (STD) Fire Extinguisher is a high-performance fire extinguisher utilizing a sodium bicarbonate-based extinguishing agent, one of the most effective agents for Class B and Class C fires.

Typical uses: For flammable liquid hazards in public areas such as offices, classrooms, multi-family residences, and parking garages. For flammable liquid fires in commercial operations such as industrial facilities, sanitation facilities, vehicle service centers, and healthcare facilities.

FEATURES

- Manufactured in accordance with ANSI/UL 299 and ANSI/UL 711 Standards.
- US COAST GUARD approved for Type B:C Size I when used in conjunction with Mounting Bracket Model A6, P/N 700270.
- DOT and TC Compliant
- Polyester epoxy powder coated steel cylinder with all-metal valve assembly, operating lever, and handle.
- Color coded pressure gauge for easy verification of pressure status.
- Trilingual labels; English, Spanish, and French.
- Rechargeable for repeated usage.
- Standard dry chemical is available in 50 lb. Pails for recharging Buckeye extinguishers.

SPECIFICATIONS

Agent Capacity: 5.5 lbs. / 2.5 kg

UL/ULC Rating: 40-B:C

Shipping Weight: 10.50 lbs. / 4.8 kg (11014)
10.75 lbs. / 4.9 kg (13514)

Height: 16.375 in / 41.6 cm

Width: 7.25 in / 18.4 cm

Cylinder Diameter: 4.25 in / 10.8 cm

Discharge Time: 14 seconds

Discharge Range: 12 - 18 ft. / 3.7 – 5.5 m

Operating Temperature Range:
-65°F to 120°F / -54°C to 49°C

Operating Pressure: 195 psi

ORDERING INFORMATION

5 LB Standard Dry Chemical Fire Extinguisher with Wall Hook- *Part No. 11014*

5 LB Standard Dry Chemical Fire Extinguisher with Vehicle Bracket- *Part No. 13514*

Note: For Coast Guard Approval, you must also order Part Number 25914