



HP 37A Black Original LaserJet Toner Cartridge (CF237A)



Overview

HP 37A LaserJet Toner Cartridge, black. Average cartridge yields 11,000 standard pages.[2]

Count on Original HP Toner cartridges with JetIntelligence to deliver high quality pages at fast speeds, plus affordable high-yield options[1] and innovative anti-fraud technology to help ensure the consistent HP quality you need.

High quality printing for workgroups

Let your cartridge manage efficient toner use and cartridge performance with page maximizer technology.

Print at high speeds—without sacrificing quality.

Continue to count on consistent quality at high speeds with Original HP Toner cartridges with JetIntelligence.

Peace of mind from cartridge authentication

Help ensure you're getting the authentic HP quality you paid for with innovative anti-fraud technology.

Toner cartridges designed for printing value

Continue to count on consistent quality at high speeds with specially formulated precision black toner.

Features



Designed to work the first time, every time^[4]



Quality prints you can take pride in



The environmental choice.^[5]



Better together. Better results.



Page maximizer technology



Black text and graphics that standout

[1] HP 37X and HP 37Y High Yield Black Original LaserJet Toner cartridges are not included in printer purchase; purchase separately. Learn more at <http://www.hp.com/go/learnaboutsupplies>.

[2] Approximate average yield based on ISO/IEC 19752. Actual yield varies considerably based on content of printed pages and other factors. For details see <http://www.hp.com/go/learnaboutsupplies>.

[4] See <http://www.hp.com/go/suppliesclaims>.

[5] HP Planet Partners program availability varies. For details, see <http://www.hp.com/recycle>. On recycled materials in cartridges, see <http://www.hp.com/go/recycledcontent>.

Specifications

Color(s) of printing supplies	Black
Print Technology	Laser
Supply type	Cartridges
Operating temperature range	15 to 30°C
Storage temperature range	-20 to 40°C
Operating humidity range	10 to 80% RH
Non-Operating Humidity Range	10 to 90% RH
Print Resolution Technologies	JetIntelligence
Compatibility	HP LaserJet Enterprise MFP M631, M632, M633 series, HP LaserJet Enterprise M607, M608, M609 series
Product count per unit	1
Quantity per pallet	60
Quantity per European pallet	36
Cartons per pallet	60
UPC number	889899204207
Minimum dimensions (W x D x H)	380 x 180 x 270 mm
Minimum dimensions (W x D x H)	14.96 x 7.09 x 10.63 in
Package dimensions (W x D x H)	380 x 180 x 270 mm
Package dimensions (W x D x H)	14.96 x 7.09 x 10.63 in
Pallet dimensions (W x D x H)	1146 x 946 x 1224 mm
Pallet dimensions	45.1 x 37.2 x 48.2 in
Package weight	~2.6 kg
Package weight	~5.72 lb
Pallet weight	176.5 kg
Pallet weight	388.2 lb
Page Yield	11000
Page yield (black and white)	~11,000 pages
What's in the box	Toner cartridge; Recycling guide
Manufacturer Warranty	This HP product is warranted to be free from defects in materials and workmanship

Additional specifications

Business filter	cMPS
Cartons per layer	15
Cartridge Colors	Black
Compatibility 01	HP LaserJet Enterprise Flow M632, M633
Compatibility 02	HP LaserJet Enterprise M607, M608, M609, M631, M632, M633
Compatibility 03	HP PageWide P57750
Compatibility headline	HP 37 toner cartridges work with:
Component type	Cartridges
Count of layers in pallet	4
Country of origin	Made in China
European pallet dimensions (W x D x H)	1128 x 746 x 959 mm
Master or single cartons per layer (European pallet)	12
Mono Starter Yield	11000
Mono yield	11000
Operating temperature range	59 to 86°F
Package count	1
Page yield (black)	1 Black (~11,000 pages)
Page yield footnote	Approximate average yield based on ISO/IEC 19752. Actual yield varies considerably based on content of printed pages and other factors. For details see http://www.hp.com/go/learnaboutsupplies .
Pallet weight	114 kg
Print technology	Laser
Product subgroup	Standard Capacity Toner Cartridges
Segment (filter)	JetIntelligence
Selectability	37A
Stacking number for pallet	16
Storage temperature range	-4 to 104°F
Subgroup	Standard Capacity Cartridges
UNSPSC code	44103103

Warranty

This HP product is warranted to be free from defects in materials and workmanship. This warranty does not apply to products that (a) have been refilled, refurbished, remanufactured or tampered with in any way, (b) experience problems resulting from misuse, improper storage, or operation outside of the published environmental specifications for the printer product or (c) exhibit wear from ordinary use. To obtain warranty service, please return the product to place of purchase (with a written description of the problem and print samples) or contact HP customer support. At HP's option, HP will either replace products that prove to be defective or refund your purchase price. TO THE EXTENT ALLOWED BY LOCAL LAW, THE ABOVE WARRANTY IS EXCLUSIVE AND NO OTHER WARRANTY OR CONDITION, WHETHER WRITTEN OR ORAL, IS EXPRESSED OR IMPLIED AND HP SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY, SATISFACTORY QUALITY, AND FITNESS FOR A PARTICULAR PURPOSE. TO THE EXTENT ALLOWED BY LOCAL LAW, IN NO EVENT WILL HP OR ITS SUPPLIERS BE LIABLE FOR DIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFIT OR DATA), OR OTHER DAMAGE, WHETHER BASED IN CONTRACT, TORT, OR OTHERWISE. THE WARRANTY TERMS CONTAINED IN THIS STATEMENT, EXCEPT TO THE EXTENT LAWFULLY PERMITTED, DO NOT EXCLUDE, RESTRICT OR MODIFY AND ARE IN ADDITION TO THE MANDATORY STATUTORY RIGHTS APPLICABLE TO THE SALE OF THIS PRODUCT TO YOU.

Weight	~4.18 lb
Weight	~1.9 kg

Disclaimer — Copyright

© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (us-en) – Nov 08, 2022 3:55 PM UTC+0000