

Door-Type Dishwashing Machines

Standard Features

- Large 27" opening for trays, sheet pans or 60-quart mixing bowl
- Adjustable cycle selector
- Automatic tank fill
- Automatic drain valve
- Door-activated cycle start
- Electric tank heat
- Low-water tank heat protection
- Pot and Pan rated
- PLC controller
- HMI Intuitive touchscreen display
- 2-Hp TEFC motor
- Door safety switch
- Interchangeable upper and lower spray arms
- Stainless steel enclosure panels
- Detergent/chemical connection provisions
- Racks: 1 peg rack and 1 flat rack

DH6000T VHR



Tall Hood Machines		Standard Voltages	Approx. Ship. Wt.
DH6000T	Electric (no booster)	208-240/60/1;	450 lbs.
	Electric (70°F rise booster)	208-240/60/3	
	ENERGY STAR® Qualified	480/60/3	
DH6000T-VHR	Electric (70°F rise booster)	208-240/60/1;	525 lbs.
	Ventless Door Machine	208-240/60/3	
	ENERGY STAR® Qualified	480/60/3	

Options

Drain Water Tempering Kit (unmounted)	
Peg or Flat Racks (specify type)	(each)
Sheet Pan Rack	(each)
Water Pressure Regulating Valve (unmounted – standard when machine has booster)	
Shock Arrestor (unmounted)	
Flanged Feet	
Splash Shield (for corner DH6000T) (mounted to machine)	
Door Interlock Switch (DH-6000T-VHR only)	
ION Scale Prevention System (unmounted)	
Chemical Pumps (detergent and rinse aid, mounted and inter-wired)	

NON STANDARD VOLTAGES: Contact Factory for availability and price. NOTE: Options prices apply only when ordered with machine.

3765 Champion Blvd, Winston-Salem, NC 27105 | 800/532-8591; Fax 336/661-1979 | ChampionIndustries.com