



DT311T Rugged Tablets

Slim, Rugged, Multi-functional Wireless Computing

The DT311 Series Rugged Tablets feature the integration of high brightness 11.6" capacitive touch screens and high performance, energy-efficient Intel® processors within slim, lightweight, durable packages. With built-in smart card/CAC reader, Wi-Fi and Bluetooth as well as options for front/ back cameras, barcode scanner, GNSS, and 4G connection, these robust tablets offer seamless information capture and transmission for improved workflow. Rated IP65 and MIL-STD-810G certified with wide temperature range (-4°F to 140°F), the DT311 Series Rugged Tablets provide reliable operation in harsh, mission-critical environments.



Features

- 11.6" high-brightness capacitive touch screen (800 nits), digital pen support
- Intel® 8th Generation Core™ i5/i7 processor
- Microsoft® Windows® 10 IoT Enterprise operating system
- NIST compliant BIOS available
- High capacity, hot-swappable battery pack
- IP65 rated, MIL-STD-810G and MIL-STD-461F certified
- Build-in smart card/ CAC reader

Major Options

- RS-232 port
- Front and back cameras
- Barcode scanner
- U-blox M8 GNSS module
- 4G LTE/AWS

Specifications

System

CPU	Intel® 8 th Generation Core™ i5 or i7 quad-core processor
RAM	8GB to 16GB
Storage	256GB to 2TB Flash
Operating System	Microsoft® Windows® 10 IoT Enterprise
NIST Compliance	NIST compliant BIOS available
Display	11.6" LED-backlight screen with capacitive touch
Display Resolution	1920 x 1080
Fan/ Fanless	Fanless
Control Switch and Buttons	1 power button, 1 trigger button, 3 programmable buttons, 1 RF switch
Indicator	1 power/ battery status LED
Microphone	Built-in microphone with DSP for real-time video
Speaker	Built-in speaker

Network Interface

WLAN	Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band
Bluetooth	Bluetooth 4.2 LE

I/O Ports

USB Ports	1 USB 3.0 and 1 USB 2.0, or can be changed to 1 USB 3.0 and 1 full size SD card slot
Headset Jack	1 (3.5mm)
DC-in	1
Ethernet	1 RJ45 connector for Ethernet
Smart Card/CAC Reader	Full-slot, reads ISO 7816 T=0, T=1; 1.8/3/5V smart card

Mechanical and Environmental

AC/DC Adapter	Input: 100-240V AC; Output: 19V DC, 3.42A
Battery Pack	Hot swappable battery, 11.4V, 5400mAh; Hot swappable battery, 11.4V, 8000mAh (optional)
Enclosure	ABS + PC plastics and magnesium-aluminum alloy
Protective Bumpers	Rubber bumpers on each corner for handling protection
Dimensions (H x W x D)	8.3 x 12.4 x 0.86 in/ 212 x 316 x 21.9 mm
Weight	3.5 lbs/ 1.6 kg
Durability	IP65, MIL-STD-810G and MIL-STD-461F certified
Regulatory	FCC Class B, CE, RoHS compliant
Temperature	Operation*: -20°C to 60°C (-4°F to 140°F), tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety, optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F). Storage: -55°C to 70°C (-67°F to 158°F)
Humidity	0% – 90% non-condensing

Major Options

Barcode Scanner	2D scanner, reads 1D also
Camera	2 megapixel front camera, and 8 megapixel back camera
GNSS Module	U-blox M8 GNSS module with concurrent reception of GPS and GLONASS; industry leading -167dBm navigation sensitivity
I/O Port Module	RS-232 port, 6-pin lockable connector included
Mobile Broadband	4G LTE/AWS

* Specifications subject to change without notice.

Accessories

Digital Pen

Pen Tip	Diameter: 0.059 in/ 1.5mm, replaceable
Buttons	2 side buttons (right-click and eraser)
Battery	1 AAAA, replaceable
Color	Black
Dimensions	Length: 5.5 in/ 140 mm (including pen tip) Diameter: 0.38 in/ 9.7 mm
Weight	0.055 lbs/ 25 g



Desktop Charging Cradle

Docking support with ports for Power, USB, HDMI outputs and Ethernet



Detachable Keyboard

Designed to connect to a DT Research Tablet, instantly pairs, ideal for 2-in-1 applications.



Tablet Mount Cradle

Offers Tablet storage and security with power, HDMI-out, COM, Ethernet pass-through, and USB ports. Power supply is not included



5-Bay Cabinet Charger

Multi-tray charger, capable of charging up to 5 tablets simultaneously



• Battery Charging Kits



• Carrying Case



• High Capacity Battery Pack

