

Item #: 236HWDD2 Project: \_\_\_\_\_

Qty: \_\_\_\_\_ Date: \_\_\_\_\_ Approval: \_\_\_\_\_



Estella Caffe

## Estella Caffe 2 Gallon Tap-Operated Digital Hot Water Dispenser - 120V, 1,500W

Item #236HWDD2



### Technical Data

Width	7 15/16 Inches
Depth	17 3/16 Inches
Height	23 3/16 Inches
Clearance Height	9 Inches
Tap Height	10 Inches
Hertz	60 Hz
Phase	1 Phase
Voltage	120 Volts
Wattage	1500 Watts
Assembly Options	Fully Assembled

### Features

- Sleek, easy-to-clean stainless steel casing and foam-insulated tank
- Digital LED temperature display
- Tap-operated dispenser with removable drip tray
- Temperature range from 140 to 206 degrees Fahrenheit
- 2 gallon capacity; 120V, 1,500W

### Certifications



5-15P



Fully Assembled



NSF Certified



UL Certified



## Technical Data

Capacity	2 Gallons
Color	Silver
Control Type	Digital
Features	NSF Certified
Material	Stainless Steel
Output	7.3 Gallons per Hour
Plug Type	NEMA 5-15P
Power Type	Electric
Style	Automatic
Temperature	140 - 206 Degrees F
Type	Hot Water Dispensers
Usage	Standard Duty
Water Inlet Size	9/16 Inches

## Notes & Details

Keep your water hot and ready to serve with this Estella Caffe hot water dispenser. This dispenser has a durable and easy-to-clean stainless steel casing for a sleek, professional look while providing ultimate reliability. It also has a foam-insulated tank to minimize energy loss and save on costs. It's perfect for cafes, coffee shops, restaurants, and convenience stores thanks to its easy-to-operate, tap-activated dispensing and minimal countertop footprint. Larger cups and mugs easily fit in the 9 5/16" space between the drip tray and tap.

It features a digital LED temperature display which functions to switch between Celsius and Fahrenheit, select your desired fill method, and choose the power setting that best suits your needs. The included removable drip tray ensures your countertops stay clean and sanitary. The 2 gallon capacity dispenses up to 7.3 gallons (156 cups) of water per hour. While the water temperature is set to a default of 203 degrees Fahrenheit, it boasts a temperature range of 140 to 206 degrees Fahrenheit. This fully assembled hot water dispenser is perfect for your countertop and requires a 120V, 1,500W electrical connection and uses a 9/16"-24 UNEF male fitting to connect it to the water line.

**⚠️ WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).