

# YOU DESERVE A RAISE

*From standard seating at lunch, bar-height for late-night, brunch buffets, or anything in between, your business can now be flexible enough for all customers and functions with the press of a lever.*



Convenient and easily adjustable, FLAT's height-adjustable tables combine one of our FLAT® Table Bases with our adjustable pneumatic post. Once installed, our pneumatic post rises or lowers with the press of a lever and the assistance of the server. Our height-adjustable tables provide restaurants and facilities with the ability to adapt to any need—and provide a simple and convenient way to cater at dining, counter or bar height—and anywhere in between. Our height-adjustable tables help operators to cater for customers with accessibility requirements and adhere with local legislation (such as ADA compliance in the USA).

Having height-adjustable table bases means you no longer need tables of varying heights for different applications, which take up storage space and your budget. As with all of our precisely engineered products, you'll be confident knowing that your tables are stable, aligned, and doing what they should—being the centerpiece of a memorable experience.



## TABLE BASES | HEIGHT-ADJUSTABLE SERIES

### FLAT® TECHNOLOGY INSTALLED BASE

Get all the benefits of having FLAT® technology under the base combined with the great possibilities that our height-adjusting post provides.



**KT22 Height-Adjustable  
(Pneumatic Post)**  
CT2067



**UR22 Height-Adjustable  
(Pneumatic Post)**  
CT3026



**UR30 Height-Adjustable  
(Pneumatic Post)**  
CT3027



**KX22 Height-Adjustable  
(Pneumatic Post)**  
CT2064



**KX2230 Height-Adjustable  
(Pneumatic Post)**  
CT2069



**KX30 Height-Adjustable  
(Pneumatic Post)**  
CT2065



**KX36 Height-Adjustable  
(Pneumatic Post)**  
CT2066

### FLAT® BOLT-DOWN MODELS

Bolts securely to the floor, providing a solid base for your customers.



**Bolt-Down Base with  
Pneumatic Post**  
CT7000



**Dual Bolt-Down Bases  
with Pneumatic Post**  
CT7001

PRODUCT	MINIMUM OPERATING HEIGHT	MAXIMUM OPERATING HEIGHT
KX22	701mm/27.6in	1035mm/40.75in
KX2230	701mm/27.6in	1035mm/40.75in
KX30	701mm/27.6in	1035mm/40.75in
KX36	701mm/27.6in	1035mm/40.75in
KT22	701mm/27.6in	1035mm/40.75in
UR22	720mm/28.3in	1054mm/41.5in
UR30	720mm/28.3in	1054mm/41.5in
Bolt-Down	671mm/26.4in	1005mm/39.6in