GARLAND

Master Series Even-Heat Hot Top Range Attachment

Project
Item
Quantity
CSI Section 11400
25. 522
Approved
Date

Models

- M6S
- M6T



Model M6S Shown with Optional Backguard

Standard Features

- Stainless steel front and sides
- Stainless steel door on storage base
- 6" (152mm) chromed steel adjustable
- 7-1/2" (191mm) stainless steel front rail
- Extra heavy cast-iron top sections
- Stainless steel burner box bottom
- Storage base interior of aluminized steel
- 17" (432mm) wide even-heat hot top steel plate
- One 30,000 BTU (8.79 kW) cast-iron burner

Options & Accessories

- Stainless steel main back
- Stainless steel common front rail up to 68" (1728mm) wide (two or more units in a battery)
- Gas regulator 3/4" or 1-1/4"
- Gas shut off valve; 3/4", 1" or 1-1/4" NPT
- Gas flex hose & quick disconnect (3/4", 1" or 1-1/4" NPT x 5') w/ restraining device, please specify
- \bullet Rear gas connection, 3/4" $\,\&$ 1" NPT $\,$
- End caps and cover (NC, specify)
- Swivel casters (4) w/front brakes
- Polyurethane non-marking swivel casters (4) w/front brakes
- 6" (152mm) stainless steel adjustable legs
- Modular stand, (T model)
- Dais base, (S model w/o legs)
- Storage base shelf of aluminized or stainless steel
- Stainless steel tubular high shelf, single or double deck
- Stainless steel backguard: 10" (354mm), 17" (432mm) or 33" (838mm) H

Specifications

Heavy-duty gas range attachment with storage base, Model M6S. One (1) even-heat hot top. 17" (432mm) wide x 38" (965mm) deep, including 7 1/2" (191mm) deep stainless steel front rail. Stainless steel front and sides. 30,000 BTU (8.79 kW) total. Natural or propane gas. Also available with modular top, suffix T.

NOTE: Attachments suppled with casters must be installed with an approved restraining device.














*Modular top has 1-1/2" seating flanges. **RC oven is 25" (635mm) deep.

INPUT-BTU/hr (Natural Gas)	M6S	M6T
Top Sections	30,000 (8.79kW)	30,000 (8.79kW)

RC=Range w/Convection Oven R=Range w/Oven S=Range w/Storage Base T=Modular Top

INSTALLATION NOTES	Shipping Wt: (Lb/Kg) - Cu Ft		
Combustible Wall Clearances 1	Entry Clearances	Operating Pressure	M6S 240/109 - 26
Sides: 14" (356mm) Back: 6" (152mm)	Crated: 22 1/4" (565mm) Uncrated: 17-1/4" (438mm)	Natural: 6" WC (15mbar) Propane: 10" WC (25mbar)	M6T 145/66 - 9

¹NOTE: Installation clearance reductions are applicable only where local codes permit.

Data applies only to North America

Gas input ratings shown here are for installations up to 2,000 ft. (610m) above sea level. Specify altitudes over 2,000 ft. Please specify gas type when ordering.

Garland/U.S. Range products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland / U.S. Range will not provide service, warranty, maintenance or support of any kind other than in commercial applications

Garland reserves the right to make changes to the design or specifications without prior notice.

