MANUAL GREASE TRAPS WITH BACTERIAL TREATMENT



BIOSERIES GGXM-35B

MANUAL GREASE TRAP WITH BACTERIAL TREATMENT

Superior Grease Management and Bio Treatment for Difficult Applications, including Coffee Shops, Ice Cream Stores, Confectionary Stores, and Restaurants



ASME A112.14.3

Grease Guardian Bio Series Grease Traps incorporate proven grease trap technology with ASME/PDI approval with our unique dry solids strainer, grease level viewing window, and highly effective GB bacterial injection system.

The bacterial digesting treatment is a non-toxic, agent which helps digest fats oils and grease while eliminating odors in the kitchen wastewater.



Grease Guardian GGXM-35B

Bio Refills are required for the **GGXM** Bio Grease Traps, available in a 3 month pack or a 12 month pack. Each refill lasts one month.

Part# Bio-GB3 - 3 Month Bio Pack comprising of 3 Bio refills and 3 sets of batteries

Part# Bio-GB12 - 12 Month Bio Pack comprising of 12 Bio refills and 12 sets of batteries

First Bio-GB3 Bio Pack is included with GGXM-35B

35 GPM - 70+ Pounds Grease Capacity



Wall Mounted Automatic
Biological Dispenser

304 Stainless Steel for superior hygiene
ASME 112.14.3 Approved
Integral Electronic Bacterial Control
Unique Dry Strainer design with front access
Globo viewing window - grease level monitoring
Fully sealed lid with quick access release clips
Compact Design for Under-sink Installations

MANUAL GREASE TRAPS WITH BACTERIAL TREATMENT




BIOSERIES - GGXM-35B


MANUAL GREASE TRAP WITH BACTERIAL TREATMENT


- Wall Mounted Automatic Biological Dispenser
- Grease Guardian Manual Grease Trap with grease level viewing window
- GGX has front access removable solids filter
- Uni-directional Inlets and Outlets conveniently located at the rear of the Grease Trap
- Hygienic Stainless Steel Grease Trap easily fts under sink / shelf



Dimensions







TECHNICAL DATA

WEIGHT 70 pounds

MATERIAL 304 Stainless steel
INTERIOR 304 Stainless steel
FLOWRATE 35 gallons per minute

GREASE RETENTION 70+ pounds
SOLIDS STRAINER CAPACITY 6.6 pounds
TANK CAPACITY 22 gallons

GGXM STANDARD FEATURES

5 Year Warranty

16 Gauge stainless steel welded tank

Fully sealed air tight system

Universal flow direction

Dry solids strainer

Integral flow control

Integral gas trap