

Glo-Ray® Curved Infrared Strip Heaters

Models:

GR5A-18, -24, -30, -36, -42, -48, -54, -60, -66, -72 GR5AH-18, -24, -30, -36, -42, -48, -54, -60, -66, -72

This stylish patented design, based on our signature Glo-Ray® strip heaters, is the perfect solution for your front-of the-house applications. Superb for buffet and serving lines, the sleek curved design minimizes its size while warming the products below.

The entire holding surface is heated evenly with no "cold" spots thanks to Hatco's dependable infrared element technology.

Hatco's wide array of colors help provide the right look for your venue.

Standard features

- Narrow, curved design: 2"H by 6"D (51 x 150 mm) uses a very small footprint.
- Lengths available from 18"-72" (457- 1829 mm) in 6" (152 mm) increments
- Patented housing design
- Pre-focused heat maintains safe serving temperatures longer without continuing to cook the food
- Available in standard or high watt
- Mounting Brackets, 3' (914 mm) Conduit and 5' (1524 mm) power leads are standard (included)
- Metal Sheathed Elements guaranteed against burnout and breakage for two years

Project			
Item#_			
Quantity			



Options	(available at time	e of purchase only)
---------	--------------------	---------------------

Housing color (Clea	r Anodized standa	ard)	
Designer Color [†]			
☐ Warm Red		☐ Gray Granite	☐ White Granite
	☐ Hunter Green	☐ Antique Copper	
Gloss Finish [†]			
	☐ Glossy Gray	☐ Bold Black	☐ Gleaming Gold
☐ Brilliant Blue			
Non-adjustalble Tub	oular Stands (Angle	e Brackets standard)	
		□ 14' (356 mm)	□ 16' (406 mm)
Designer Cold	or [†]	,	, ,
□Warm Red	I □Black	☐ Gray Granite	□ White Granite
□ Navy Blue	☐ Hunter Gre	en 🗆 Antique Coppe	r

□ Radiant Red □ Glossy Gray □ Bold Black □ Brilliant Blue

Power Wire Lead Length – 5' (1524 mm) is standard □ 6' (1829 mm) □ 7' (2134 mm) □ 8' (2438 mm) □ 9' (2743 mm) □ 10' (3048 mm)

[†]Non-standard colors are non-returnable

Gloss Finish[†]








☐ Gleaming Gold



Glo-Ray® Curved Infrared Strip Heaters

Models: GR5A-18, -24, -30, -36, -42, -48, -54, -60, -66 -72 GR5AH-18, -24, -30, -36, -42, -48, -54, -60, -66 -72

GR5A, GR5AH



SPECIFICATIONS

Glo-Ray® Curved Infrared Strip Heaters
Phase: Single

Standard Watt			High Watt			All Models			
Model	Volts	Watts	Amps	Model	Volts	Watts	Amps	Dimensions W x D x H	Weight*
GR5A-18	120 208 240	250	2.1 1.2 1.0	GR5AH-18	120 208 240	350	2.9 1.7 1.5	18" x 6" x 2" (457 x 150 x 51 mm)	13 lbs. (6 kg.)
GR5A-24	120 208 240	350	2.9 1.7 1.4	GR5AH-24	120 208 240	500	4.2 2.4 2.1	24" x 6" x 2" (610 x 150 x 51 mm)	14 lbs. (7 kg.)
GR5A-30	120 208 240	450	3.8 2.2 1.9	GR5AH-30	120 208 240	660	5.5 3.2 2.8	30" x 6" x 2" (762 x 150 x 51 mm)	15 lbs. (7 kg.)
GR5A-36	120 208 240	575	4.8 2.8 2.4	GR5AH-36	120 208 240	800	6.7 3.8 3.3	36" x 6" x 2" (919 x 150 x 51 mm)	17 lbs. (8 kg.)
GR5A-42	120 208 240	675	5.6 3.2 2.8	GR5AH-42	120 208 240	950	7.9 4.6 4.0	42" x 6" x 2" (1067 x 150 x 51 mm)	18 lbs. (9 kg.)
GR5A-48	120 208 240	800	6.7 3.8 3.3	GR5AH-48	120 208 240	1100	9.2 5.3 4.6	48" x 6" x 2" (1219 x 150 x 51 mm)	20 lbs. (9 kg.)
GR5A-54	120 208 240	925	7.7 4.4 3.9	GR5AH-54	120 208 240	1250	10.4 6.0 5.2	54" x 6" x 2" (1372 x 150 x 51 mm)	21 lbs. (10 kg.)
GR5A-60	120 208 240	1050	8.8 5.0 4.4	GR5AH-60	120 208 240	1400	11.7 6.7 5.8	60" x 6" x 2" (1524 x 150 x 51 mm)	22 lbs. (10 kg.)
GR5A-66	120 208 240	1160	9.7 5.6 4.8	GR5AH-66	120 208 240	1560	13.0 ≻ 7.5 6.2	66" x 6" x 2" (1675 x 150 x 51 mm)	24 lbs. (11 kg.)
GR5A-72	120 208 240	1275	10.6 6.1 5.3	GR5AH-72	120 208 240	1725	14.4 ≻ 8.3 7.2	72" x 6" x 2" (1829 x 150 x 51 mm)	25 lbs. (12 kg.)

^{*} Weights are approximate and do not include shipping materials.

RECOMMENDED MOUNTING HEIGHTS

(Refer to the Installation section in the Installation and Operating Manual on the Hatco website) Make sure countertop material is designed to withstand long periods of hot food holding temperatures. Contact manufacturer of countertop material for application information.

GR5A Series strip heaters can be installed over a steam table. Follow the minimum clearance requirements for non-combustible surroundings.

Combustible surroundings (GR5A only)

Below overshelf:1" (25 mm) clearance Unit to surface below: 11" (279 mm) Back to wall: 1" (25 mm)

Non-Combustible surroundings (GR5A, GR5AH)

Below overshelf:1" (25 mm) clearance Unit to surface below: 10" (254 mm) Back to wall: 0" (0 mm)

REMOTE CONTROL ENCLOSURES

RMB series uses one Control Box per Strip Heater - If RMB2 series is used, multiple warmers can be controlled from one box (U.S., Canada only). For more details, see "Choose Remote Box" section listed under "Resources" on the Hatco website, or consult Price List.

Model	Width (W x D x H)				
RMB-3A	_				
RMB-3B					
RMB-3C	5.51010.51				
RMB-3D	5.5" x 3" x 2.5" (140 x 76 x 64 mm)				
RMB-3F	(140 x 70 x 04 11111)				
RMB-3G					
RMB-3H					
RMB-7F	9" x 3" x 2.5"				
RMB-7G					
RMB-7H	(229 x 76 x 64 mm)				
RMB2-1R	11" x 4.5" x 5.5" (280 x 115 x 140 mm)				
RMB2-2R	14" x 4.5" x 5.5" (356 x 115 x 140 mm)				

PRODUCT SPECS

Glo-Ray® Slim Curved Strip Heater
The Curved Infrared Strip Heater shall be a Glo-Ray®, manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A.

The Foodwarmer shall be a Glo-Ray model ... , rated at ... watts, ... volts, single phase and be ... inches (millimeters) in overall width.

The Glo-Ray shall consist of Clear Anodized, Designer or Gloss Finish painted patented housing and include as standard equipment 3' (914 mm) conduit with 5' (1524 mm) power leads and mounting brackets. The infrared heating element shall be tubular metal sheathed. The foodwarmer shall be factory assembled ready for electrical installation.

Options shall include choice of Designer color or Gloss Finish, extended power leads and Non-adjustable Tubular Stands.

Comes with 24/7 parts and service assistance (U.S. and Canada only).

HATCO CORPORATION P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A.

(800) 558-0607 | (414) 671-6350 | www.hatcocorp.com | equipsales@hatcocorp.com | intlsales@hatcocorp.com

> Infinite switch not available