

# **HEAVY DUTY ICE-COOLED TABLES**



## WITH ENCLOSED BASE AND SLIDING DOORS



**HDCPU-3-DR Shown** 

ltem #:	Qty #:
Model #:	
Project #:	

Model	Length (L)	Width	O.A. Inside Well Dim (A x B)	Wt (Ibs.)	Cu. Ft.
HDCPU-2-DR	31.8125"	28.25"	24.125" x 19.25"	127 lbs.	27
HDCPU-3-DR	47.125"	28.25"	39.50" x 19.25"	155 lbs.	39
HDCPU-4-DR	62.50"	28.25"	54.75" x 19.25"	215 lbs.	58
HDCPU-5-DR	77.75"	28.25"	70" x 19.25"	264 lbs.	69
HDCPU-6-DR	93.125"	28.25"	85.375" x 19.25"	309 lbs.	81

#### **FEATURES:**

Heavy duty construction

All welded 300 series stainless steel

Fiberglass insulation

Two stainless steel sliding doors

Uses standard 12" x 20" pans, and smaller pans with the use of adapter bars (NOT INCLUDED)

Stainless steel shelf with removable 3/8" thick poly cutting

board - Ships K.D.

#### **MATERIAL:**

CABINET BASE: 18 gauge #304 stainless steel

LINER: 8" deep, 18 gauge #302 stainless steel welded

**CUTTING BOARD: White Thermoplastic** 

**INSULATION:** Fiberglass

LEGS: 16 gauge stainless steel with full adjustable

stainless steel bullet foot

## **Food Table Shelving & Accessories**

Visit our website for additional accessories



### Double Sided Self-Serve Buffet Shelf

with Built-In Food Shield

Model	Length	Approx Wt.	Cu. Ft.
TBS-2	31-13/16"	34 lbs.	2
TBS-3	47-1/8"	42 lbs.	3
TBS-4	62-7/16"	47 lbs.	4
TBS-5	77-3/4"	55 lbs.	4
TBS-6	93-1/8"	63 lbs.	4



#### **Acrylic Side Panels** for Buffet Shelf

Add side panels to meet additional NSF requirements (2 panels per end)

TBP-1 One End TBP-2 Two Ends

Field Installation Available



15" Height

Acrylic Food Shield has 1" Clearance from Deck

## Single Sided Cafeteria Shelf

with Built-In Food Shield

Model	Length	Approx Wt.	Cu. Ft.
TSS-2	31-13/16"	18 lbs.	2
TSS-3	47-1/8"	23 lbs.	3
TSS-4	62-7/16"	30 lbs.	4
TSS-5	77-3/4"	35 lbs.	4
TBS-6	93-1/8"	41 lbs.	4



### **Acrylic Side Panel** for Serving Shelf

Add side panels to meet additional NSF requirements. (1 panel per end)

TSP-1 One end TSP-2 Two Ends Field Installation Available



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

# **DIMENSIONS and SPECIFICATIONS**

TOL ± .125" ALL DIMENSIONS ARE TYPICAL



