



## Heavy Duty High Flow

Buckeye's Heavy Duty High Flow product line of fire extinguishers go where other fire extinguishers fear to tread. Designed for installations in harsh, unforgiving environments, the Buckeye Heavy Duty High Flow extinguishers not only meet the demands where NFPA 10 requires the installation of high flow extinguishers, installations where hazards such as pressurized flammable liquids, pressurized gas, or three dimensional fires exist, but they are also equipped with additional features that make them less susceptible to damage and wear that would take other extinguishers out of service.

### Key Features

- Exceeds UL and NFPA requirement for 1 lb. per second discharge rate
- Rugged steel cylinders and nickel-plated brass valves
- Galvanizing compound coating with a baked-on polyester epoxy finish coat provides unmatched corrosion protection - passes 3000 hr salt spray test
- Stainless Steel operating handles and Pull Pin
- Plated brass gauge guard and protective vinyl foot ring
- UL and ULC Listed
- Meets DOT and TC requirements
- US Coast Guard Approved with listed marine bracket
- Trilingual labels-English, Spanish, and French
- Widest selection of agents and sizes in the industry
- Operating temperature is -65°F to 120°F
- Operating pressure 195 psi

Third Party Approvals For Peace Of Mind



Model	10 HDHF ABC	10 HDHF PK	10 HDHF STD	13 HDHF ABC	13 HDHF PK	13 HDHF STD	20 HDHF ABC	20 HDHF PK	20 HDHF STD	30 HDHF ABC	30 HDHF PK	30 HDHF STD
Pt. #	11351	11651	11851	11151	11251	11451	12351	12651	12851	13351	13651	13851
Agent Capacity	10 Lbs. (4.54 kg)	10 Lbs. (4.54 kg)	10 Lbs. (4.54 kg)	13.2 lbs. (6 kg)	13.2 lbs. (6 kg)	13.2 lbs. (6 kg)	20 lbs. (9.07 kg)	20 lbs. (9.07 kg)	20 lbs. (9.07 kg)	30 lbs. (13.6 kg)	30 lbs. (13.6 kg)	30 lbs. (13.6 kg)
UL/ULC Rating	1-A:20-B:C	20-B:C	10-B:C	1-A:20-B:C	20-B:C	10-B:C	4-A:60-B:C	60-B:C	60-B:C	4-A:80-B:C	80-B:C	60-B:C
Discharge Rate (lb/sec)	1.11	1.03	1.17	1.26	1.11	1.25	1.17	1.57	1.34	1.43	1.56	1.75
Discharge Time (Secs)	10	10	9	11	12	10	18	13	14	22	21	17
Discharge Range ft (m)	30-40 ft (9.14-12.19m)	30-40 ft (9.14-12.19m)	30-40 ft (9.14-12.19m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)	40-50 ft (12.19-15.24m)
USCG Approval	Type A Size II Type B:C Size II	Type B:C Size II	Type B:C Size II	Type A Size II Type B:C Size II	Type B:C Size II	Type B:C Size II	Type A Size II Type B:C Size III	Type B:C Size III	Type B:C Size III	Type A Size II Type B:C Size IV	Type B:C Size IV	Type B:C Size IV
Shipping Wt. (lbs.)	19.5	19.5	19.5	26	26	26	35.5	35.5	35.5	49.5	49.5	49.5
Unit Height (in.)	17	17	17	17.75	17.75	17.75	21.5	21.5	21.5	27.5	27.5	27.5
Unit Width (in.)	8.25	8.25	8.25	8.25	8.25	8.25	8.75	8.75	8.75	8.75	8.75	8.75
Unit Diameter (in.)	6.5	6.5	6.5	7.5	7.5	7.5	8	8	8	8	8	8