

HVTC HIGH VELOCITY TRUCK COOLER



COMPARED TO PREVIOUS GENERATION 115V HVTC

- 2x airflow velocity at bulkhead
- 38% lower motor amps
- 68% quieter
- 27% lighter



Optional Integrated LED Lights



			FAN DIMENSIONS			AIR THROW	UNIT
MODEL	CFM	HP	W	D	Н	DISTANCE	WEIGHT
HVTC	3200	1/2	16"	26"	17.5"	120'	42 lbs

FEATURES

Wheel (Blower): 9.5" X 11"

Fan Housing: High Impact Polypropylene

Inlet Guards: .5" Opening
Outlet Guards: .5" Opening
Mounts: Fixed 90° or Swing Arm

RPM: 1075 Decibels: 75 @ 3' Enclosure: ODP Standard

Frame: 48

Ambient Temperature: 104°F Duty Cycle: Continuous Warranty: 2 Years

OPTIONAL LED LIGHTS

Lumens: 3100 Wattage: 28W CCT: 6500K

CRI: 70+

Operating voltage: 100-277 Frequency: 50/60Hz

MOTOR

VOLTAGE	MOTOR AMPS	RUNNING AMPS
115V 1Ø	6.2	5.5
208V 1Ø	2.7	2.5
277V 1Ø	2.6	2.6
460V 3Ø (3/4 HP)	1.5	1.4

