

ICE CHESTS

STANDARD, WITHOUT COLD PLATE



JOB	
AREA	
ITEM NO.	
MODEL NO.	

MODELS	
TS Series	TSD Series
TS18IC	TSD18IC
TS24IC	TSD24IC
TS30IC	TSD30IC
TS36IC	TSD36IC
TS42IC	TSD42IC
TS48IC	TSD48IC



Perlick Features

- Dent resistant ABS top ledge
- Stainless steel legs install without tools and have rust-free thermoplastic feet



ICE CHESTS
STANDARD, WITHOUT COLD PLATE

MODEL NOS.	TS(D)18IC	TS(D)24IC	TS(D)30IC	TS(D)36IC	TS(D)42IC	TS(D)48IC
LENGTH IN. (mm)	18 (457)	24 (610)	30 (762)	36 (914)	42 (1067)	48 (1219)
ICE CAP. lbs. (kg)	35 (15.8)	50 (22.7)	70 (31.8)	85 (38.6)	100 (45.4)	115 (52.2)
SHIP WT. lbs. (kg)	50 (22.7)	60 (27.2)	70 (31.8)	80 (36.3)	90 (40.1)	100 (45.4)
FRONT & SIDES	Stainless steel, top rim ABS					
BACKSPLASH	General and TS Series: Stainless steel 6" high (4" optional) with 1" return at top, mechanically fastened and sealed to ice chest top with steel support brackets TSD Series: Backlash and rear deck stainless steel					
BACK & BOTTOM	Galvanized steel					
COVERS	Stainless steel, two-piece, removable					
INTERIOR	Stainless steel with 1/4" radius corners, welded and sealed. Interiors can be divided with accessory freestanding ice dividers					
INSULATION	Foamed-in-place polyurethane					
LEGS	1-5/8" tubular, stainless steel with 1" adjustable thermoplastic foot (4 legs are standard)					
PLUMBING	Drain connection- 1/2" NPS male					

Note: Covers not included.

