



## **Infrared Thermometer, Timer & Clock**

## Model: IN482

With a fast one-second response, provides surface at the push of a button. Shows minimum/maximum temperatures, and locks for continuous temperature reads. Stopwatch timer. Clock and ambient temperature in standy mode. Distance:spot ratio of 5:1.



		<ul> <li>S</li> </ul>
	IN482 replaces >	• IN428
Features	One-button operation, hold mode, maximum, minimum and lock for continuous scanning, stopwatch timer, clock, ambient temperature battery status indication	One-button operation, hold mode, maximum, minimum and lock for continuous scanning, battery status indication
Certification	WEEE, CE, RoHs, REACH	WEEE, CE
Measurement Range	-67 to + <b>482</b> °F/-55 to +250°C; 24 hours by hr/min/ sec	-67 to +428°F/-55 to +220°C
Unit of Measure	Thermometer: °F/°C; clock: hour/minute; stopwatch timer: hour/minute/second	°F/°C
Accuracy	-67 to +32°F/-55 to 0°C: $\pm$ (3.6+0.09/ deg)°F/ $\pm$ (2+0.05/deg)°C; above 32°F/0°C: $\pm$ 3.6°F/2°C or $\pm$ 2% of the reading, whichever is greater	±1.1°F/±0.6°C
Distance:Spot	5:1	1:1
Emissivity	0.95 default - adjustable 0.05 to 1	0.05~1, Step .01
Spectral Response	8~14 μm	
Response Time	1 second response	1 second response
On/Off	On: SCAN button	On: SCAN button
Auto-off	Auto-off after 15 seconds	Auto-off after 15 seconds
Housing Material	Food-safe ABS	Food-safe ABS
Display Material	LCD	LCD
Display Size	1.08 W x 0.65 H (in)/2.75 W x 1.65 H (cm)	0.883 W x 0.568 H (in)/2.2 W x 1.4 H (cm)
Resolution	Thermometer: -9.9 to 199.9°F/°C: 0.1°F /°C, otherwise 1°F/1°C; stopwatch timer: 0 to 30 minutes: 0.01 second, 3 minutes to 24 hours: 0.1 second	0.1°F/0.1°C
Casing		Pouch
Mounting	Stand/loop	Wrist strap
Operating Range	14 to +122°F/-10 to +50°C	14 to +122°F/-10 to +50°C
Battery	One 3V IEC CR2032 lithium button battery included	One 3V IEC CR2032 lithium button battery included
Battery Life	40 hours continuous use	40 hours continuous use
Dimensions	1.65 W x 2.94 H x 0.79 D (in)/ 4.2 W x 7.473 H x 2.012 D (cm)	1.5 W x 3.0 H x 0.75 D (in)/ 3.9 W x 7.68 H x 1.93 D (cm)
Weight	1.0 oz / 28 g (including battery)	1.6 oz / 45.4 g (including battery)
Warranty	1-Year Limited Warranty	1-Year Limited Warranty