
## ITB w/Display Group

Height: 35.0" Width: 11.6" Depth: 23.7" (88.9cm) (29.5cm) (60.2cm)





- Sleek, modernized design language on the brewer, with rounded angles on the corners and trunk
- Digital readout displays in English, Spanish, or French ---for easier programming and control--- and can show either 'Standard' or Metric measurements. Digital readout also shows machine status, and targeted advertising messages can be programmed for display.
- BUNN Infusion Series technology allows for multiple recipes from one footprint --with three brew buttons and two batch sizes
- Easy pulse display allows for simplified programming of pulse routine
- Energy-saver mode reduces tank temperature during idle periods
- Exclusive Peak Extraction™ Sprayhead is multi-directional with a 7-hole design to ensure ultimate uniformity of extraction
- Electronic funnel lock prevents removal of each brew funnel until drip-through is complete
- USB programming capable
- Brew counter keeps track of how many batches are brewed
- Pre-infusion and pulse brew for maximum flavor extraction. Cold brew lockout & digital temperature control further ensure top-notch brewing.
- Includes overlay kit for customization of brewer interface

#### Agency:





#### **Specifications**

Product #: 52000,0000

Finish: Stainless

Funnel: Translucent Tea Funnel

Water Access: Plumbed

#### **Additional Features**

Funnel Locks

### **Electrical & Capacity**

120	14		1700	Yes	NEMA 5-15P	672	60°F (15.5°C)	4	2	60
Volts	* Amp	os	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H <sup>2</sup> O Temp.	Phase	# Wires plus Ground	Hertz

\*When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

#### Plumbing Requirements


PSI kPa		kPa	Fitting Supplied	Water Flow Required (GPM)					
	20-90	138-621	3/8" BSPP	1.25					


## CAD Drawings


2D	Revit	KLC
•		


WARNING: This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov











Unit				Shipping				
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	35.0 in.	11.6 in.	23.7 in.	35.0 in.	11.6 in.	23.7 in.	41.600 lbs	7.976 ft³
Metric	88.9 cm	29.5 cm	60.2 cm	88.9 cm	29.5 cm	60.2 cm	18.870 kgs	0.226 m³



## Related Products & Accessories: ITB w/Display Group(52000.0000)















# Serving & Holding Options: ITB w/Display Group(52000.0000)



TD4, SIGHT GAUGE SWT/UNSWT HDL

Product #:03250.0003



TDO-5, RESERVOIR, BREW THRU

Product #:34100.0003



TDO-N-3.5, RSVR

Product #:39600.0001



TDO-N-4.0, RSVR BUNN

Product #:39600.0002



TDO-N-3.5, RSVR W/ LIFT HANDLE

Product #:39600.0031



TDO-N-3.5, RSVR W/ PINCH TUBE

Product #:39600.0047



TDO-N-3.5, W/BREW THRU LID

Product #:39600.0081



TDO-N-3.5,RSVR W/ PINCHTUBE/BREW THRU LID

Product #:39600.0083



TD3T-N, RSVR BREW THRU LID BUNN

Product #:43900.0001



TD3T-N, RSVR SOLID LID BUNN

Product #:43900.0002