

SensorSAFE[™] infrared dispense (optional)



SensorSAFF not recommended for use with clear containers or for applications in direct sunlight

Ice and water dispensers, 115V/60 Hz					
Ice storage capacity	Dispense	lce machine cooling	Item number		
90 lb (40.9 kg)	Lever	air	110CT425A-L		
		water	110CT425W-L		
	SensorSAFE	air	110CT425A-S		
		water	110CT425W-S		

Ice-only available, add -I Example: 110CT425A-LI

	Ice production				
	Temperatures air/water	70/50 F (21/10 C)	90/70 F (32/21 C)		
	Air-cooled	425 lb (193.0 kg)	325 lb (147.6 kg)		
	Water-cooled	486 lb (220.6 kg)	408 lb (185.2 kg)		
	Energy consumption per 100 lb (45.4 kg) ice	N/A	6.3 kWh air-cooled 4.3 kWh water-cooled		
	Condenser water consumption	N/A	0.5 gpm (1.9 Lpm) at 70 F (21 C) water		
Water 12.0 gal (45.4 L) of potable water per consumption (45.4 kg) of ice		table water per 100 lb			

$Symphony\ Plus^{^{\mathsf{TM}}} \mathsf{ice}\ \mathsf{and}\ \mathsf{water}\ \mathsf{dispenser}$

110 CT series countertop with Chewblet® ice machine

Features

90 lb (40.9 kg) ice storage capacity

Removable air- or water-cooled ice machine with up to 425 lb (193.0 kg) daily production of popular Chewblet ice

- soft, chewable, compressed nugget ice is preferred over cubes¹ and is ideal for patient care
- Quiet Night[™] sleep mode turns off ice machine when idle

Designed with sanitation in mind



- automatic self-flushing of ice machine removes impurities
- drain cup provides internal air gap for added protection of food zone components from drain line contaminants
- Agion® silver-based antimicrobial provides protection of key ice and water contact components²
- one-hand lever or SensorSAFE infrared ice dispense

Dependable design, easy to service and clean



- cleaning and sanitizing of entire machine takes only 1 hour
- LED control board provides at-a-glance machine status
- panels are easily removed for accessibility to all components
- ice machine parts are common across all Symphony Plus dispensers
- stainless steel evaporator and auger deliver long life

Environmentally responsible

- meets Consortium for Energy Efficiency Tier 2 specifications
- R404a refrigerant has zero ozone depletion potential
- ice-only dispensers are ENERGY STAR® certified
- continuous ice making process uses less electricity and water

Durable, attractive dispenser

- frame and exterior cabinet are stainless steel with accent trim
- poly drain pan, grille and dispenser lid are corrosion-resistant

New

- secured top lid

Easy installation and industry's best warranty

- comes in two boxes ice machine and dispenser
- warranty 3 years parts and labor, 5 years compressor parts

Accessories

BS - Base stand (item# 01049832)

Chilled water option (item# 01063205)

SafeCLEAN™ environmentally responsible ice machine cleaner (item# 00132001)

Nu-Calgon® IMS-II sanitizer, 16 oz bottle (item# 00979674)

Additional filters (refer to form# 6380, 9905, 6070)

Additional Symphony Plus accessories (refer to price list)



Specification		
Ice storage capacity	90 lb (40.9 kg)	
W1 Width, dispenser	25.00" (63.5 cm)	
W2 Width, base stand accessory	26.25" (66.7 cm)	
D1 Depth, dispenser	28.75" (73.0 cm)	
D2 Depth, drain pan	7.00" (17.78 cm)	
D3 Depth, base stand accessory	29.00" (73.7 cm)	
H1 Height, dispenser	53.00" (134.6 cm)	
H2 Dispense height clearance	7.75" (19.68 cm)	
H3 Height, base stand accessory	33.00" (83.8 cm)	
Ventilation clearance	air-cooled models only – 6.00" (15.24 cm) top	
Service clearance	12.00" (30.5 cm) top	
C1 115 V/60/1 dispenser electrical	11 amps, 0.8 kW 7' (2.1 m) cord, NEMA 5-15 90° hospital-grade plug.	
Utility connection location	internal connection	
C2 Potable water inlet, dispenser	3/8" FPT	
C3 Drain, dispenser	3/4" MPT	
C4 Potable water inlet, ice machine	3/8" FPT internal connection – 1.5" (3.81 cm) knockout provided in back or bottom	
Water-cooled ice machine connections		
C5 condenser inletC6 condenser drain	3/8" FPT 3/8" FPT	
C7 Drain, ice machine	3/4" MPT	
Air temperature	50 -100 F (10 - 38 C)	
Water temperature	45 - 90 F (7 - 32 C)	
Water pressure	10 - 70 psi (69 - 483 kpa)	
Heat rejection	air-cooled models – 5000 BTU/hr, water-cooled models – 1400 BTU/hr to air, 3600 BTU/hr to water	
Water flow requirement for water- cooled models	0.25 gpm at 50 F 0.5 gpm at 70 F 1.25 gpm at 90 F	
Approximate ship weight	290 lb (132 kg) (two boxes)	
Approximate ship weight, base	140 lb (64 kg)	


NOTE: For indoor use only


stand accessory

SHORT FORM SPECIFICATION: (Choose one) ___ lce and water or __ ice-only dispenser to be Follett® automatic load in countertop configuration, with 90 lb (40.9 kg) of storage. Environmentally responsible R404a ice machine to be (choose one) __ air- or __ water-cooled and to be removable for cleaning and maintenance. Dispenser frame and cabinet to be stainless steel with plastic trim. Ice machine to produce approximately 425 lb (193.0 kg) of Chewblet compressed nugget ice at air temp. of 70 F (21 C), water temp. of 50 F (10 C). Ice machine to be equipped with automatic self-flushing and Quiet Night sleep mode. Storage area to be insulated with non-CFC, high density, foamed-in-place polyurethane.

7' (2.1 m) cord and NEMA 5-15 90° hospital-grade plug provided. NSF and ETL listed.

Dimensional drawing





BS*– Base stand sold separately; measurements shown are with base stand legs at lowest position
See dispenser detail sheet, form# 6675, for counter cut outs.

- 1 Independent third party studies. Contact Follett for details.
- 2 Disclaimer: Antimicrobial protection is limited to the treated components and does not treat water or ice.

Agion is a registered trademark of Sciessent LLC.
ENERGY STAR and the ENERGY STAR mark are registered US marks.
Calgon is a licensed tradename distributed by Nu-Calgon, in the United States.
Symphony Plus, SensorSAFE, SafeCLEAN and Quiet Night are trademarks of Follett Corporation.
Chewblet and Follett are registered trademarks of Follett Corporation, registered in the US.
Follett reserves the right to change specifications at any time without obligation. Certifications may vary depending on country of origin.





