

www.doyon.qc.ca • www.nu-vu.com

JA14

JET-AIR OVEN

The JA series from Doyon is known worldwide for its unique JET AIR SYSTEM. The air moves in one direction, stops then moves the other way resulting in a bidirectional and gentle velocity air flow for exceptional baking results. This system will help you bake faster and more evenly without having to turn pans during baking time. The Jet Air fan system will save energy and labor costs.

The JA14 provides great flexibility in terms of range of products that can be baked or cooked. It features a programmable or manual one shot and constant pulse steam injection. To get the results you really want, we have added as standard a fan delay for those delicate products.



JA14

STANDARD FEATURES

OVEN

- Outstanding steam shot and pulse injection system
- Reversing fan system
- Two speeds fan
- Fan delay switch
- · High production oven
- Manual mode and user friendly EBake programmable control up to 99 recipes
- Digital temperature control up to 500°F
- · Digital reminder timer
- USB Port
- Brightly lit, compact space saving unit
- Full view heat reflective thermal glass doors
- · Fully insulated, completely sealed
- Energy efficient electric or gas heating (baking temperature reached in 15 minutes)
- Magnetic latches
- · Door switch cutoff for fan blower

- Stainless steel inside and outside
- 3/4 HP motor
- 2 year parts 1 year labor limited warranty

OPTIONS

- Perforated nickel plated pizza decks
- High temperature gasket for baking over 400°F (250°C)
- · Water softener: PLF240
- Gas quick disconnect kit (4' (1120 mm) flexible hose, ball valve and securing device)

Experience our top-of-the-line ovens today!



5600 13th Street • Menominee, MI 49858 USA

OVERALL DIMENSIONS

JA14 38 1/2" W X 49 1/4" D X 73" H (978 mm X 1251 mm X 1854 mm) JA14G 38 1/2" W X 53 5/8" D X 73" H (978 mm X 1362 mm X 1854 mm)

OVEN INTERIOR DIMENSIONS

JA14 25 1/2" W X 30 1/2" D X 28" H (648 mm X 775 mm X 711 mm) JA14G 25 1/2" W X 29 1/2" D X 28" H (648 mm X 749 mm X 711 mm)

Shelf spacing 3 1/4" (83 mm)

ELECTRICAL SYSTEM JA14

1 Phase:

208V - 103 A - 21.5 kW - 60 Hz - 2 wires + Ground 240V - 90 A - 21.5 kW - 60 Hz - 2 wires + Ground

3 Phases:

208V - 66 A - 21.5 kW - 60 Hz - 3 wires + Ground 240V - 58 A - 21.5 kW - 60 Hz - 3 wires + Ground

Other voltages available

GAS SYSTEM

JA14 (Propane or natural)

BTU total: 130 000 (65 000 per section)

Voltage:

120/240V - 1PH - 9A - 1.7 kW - 60Hz - 3 wires + Ground 120/208V - 1PH - 9A - 1.7 kW - 60Hz - 3 wires + Ground

Gas inlet: 1/2" NPT
Draft hood: 6" (152 mm)
Recommended gas pressure:
Propane gas: 11" W.C.
Natural gas: 7" W.C.

WATER INLET: 1/4" NPT

Minimum clearance from combustible material 1" (25 mm) side and back 4" (102 mm) on non combustible floor 12" (305 mm) top

FINISH: Stainless steel

SHIPPING WEIGHT


JA14 1135 lb (515 kg) approximately JA14G 1300 lb (590 kg) approximately


CAPACITY


Standard sheet pans 18" X 26" (457 mm X 660 mm): 14 pans Four-strapped bread pans: 56 loaves 9" (230 mm) pies: 98 pies

Electrical service connection and water inlet are located at the back of the unit. Specifications and design are subject to change without notice.

JA14







JA14G

