



ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON

DIMENSION TOLERANCE ± 1/4"

- STANDARD FEATURES**
- MODEL NUMBER IS JIB-LC-6
 - CAPACITY IS 600 LBS.
 - OVERALL WIDTH IS 8"
 - OVERALL JIB LENGTH IS 96 1/8"
 - OVERALL I-BEAM LENGTH IS 88"
 - USABLE I-BEAM LENGTH IS 80"
 - OVERALL HEIGHT IS 63 1/4"
 - UNDER I-BEAM HEIGHT IS 57 1/4"
 - I-BEAM SIZE: 6" HEIGHT X 4" FLANGE WIDTH
 - 180° I-BEAM ROTATION
 - TOUGH BAKED IN POWDERCOAT BLUE FINISH
- SPECIAL FEATURES**
- NONE

APPROVAL

I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.
UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-RETURNABLE
☐ As drawn ☐ As marked
Signed: _____ Date: _____
Printed Name: _____
LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING

DISTRIBUTOR'S NAME:		P.O.#
VESTIL MANUFACTURING		X
DRAWN BY: ND		W.O.#
DATE: 6/4/2007		X
REFERENCE: X	SCALE: 1:19	SALES: X
QUOTED LEAD TIME: X	QUOTE # X	FILE NAME:
		28-007-033