PRODUCT SPECIFICATIONS

Elkay Scrub/Handwash Wall Mount Faucet. Faucet has a flow rate of 2.2 GPM, and . Faucet requires 2 faucet holes.

Mounting Type:	Wall Mount
Finish:	Chrome (CR)
Handle Type:	2" Lever Handle
Deck Clearance:	5-3/8"
Spout Reach:	3-1/2"
Spout Height:	8"
Hole Drillings:	2
Valve Connection:	1/2"-14 NPSM
Flow Rate:	2.2 GPM
Faucet Hole Size (min):	1-1/8"
Faucet Hole Spread:	4
Spout Type:	Bubblers + Other

Chrome (CR)

A Century of Tradition and Quality.
For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.

Product Compliance: ADA & ICC A117.1
ASME A112.18.1/CSA B125.1
NSF 372 (lead free)
NSF 61

Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards.

Clean and Care Manual (PDF)
Warranty (PDF)

Dimensions: 1-15/16" (49mm), 3-1/2" (89mm), 5-3/8" (136mm), 3" (78mm), 8" (203mm), 2-1/2" (63mm), 4" (102mm)

PART:_____QTY: _____

PROJECT:_____

CONTACT:_____

DATE:_____

NOTES:_____

APPROVAL:_____

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

Elkay REV 07292022

LKB400

1-800-476-4106

CustCare@Elkay.com

© 2022   Page 2

LKB400_spec.pdf