



Project _____

Item 541HTDT403 Quantity _____

Approval _____ Date _____

MainStreet Equipment HTDT Single Rack High-Temperature Door-Type Dish Machine with Booster Heater - 208-240V, 3 Phase

Item #541HTDT403

Special Features

- Efficient unit uses only .53 gallons of water per cycle
- Cleans up to 40 racks; 1440 dishes per hour
- Four cycle options with varying wash times
- Digital display provides convenient readout of temperature, errors, and functions
- 208-240V, 3 phase; field convertible to 1 phase

Technical Data

| | |
|------------------------------|---------------------------|
| Width | 28 Inches |
| Depth | 32 3/8 Inches |
| Height | 57 11/16 - 76 5/16 Inches |
| Power Cord Length | 6 Feet |
| Dishwasher Height | Standard |
| Hertz | 60 Hz |
| Phase | 3 Phase |
| Voltage | 208 - 240 Volts |
| Application | Dishwashers |
| Booster Tank Capacity | 2.4 gal. |



Certifications



ETL Sanitation



ETL, US & Canada



3/4" Water
Connection




Hardwired



Field Convertible
(Electrical)

Technical Data

| | |
|---------------------------------|---|
| Booster Wattage | 9.8 Kilowatts |
| Dishes Per Hour | 1440 Dishes |
| Dishwasher Style | Straight |
| Features | Booster Heater Included Field-Convertible (Electrical) |
| High or Low Temp | High Temp |
| Horsepower | 1 hp |
| Interior Clearance | 17 Inches |
| Minimum Water Inlet Temperature | 120 Degrees F |
| Number of Cycles | 4 Cycles |
| Plug Type | Hardwire |
| Racks Per Hour | 40 |
| Type | Single Rack |
| Wash Cycle Time | 90 / 120 / 180 / 600 Seconds |
| Wash Tank Capacity | 8.7 gal. |
| Water Inlet Size | 3/4 Inches |
| Water Temperature | 150 - 180 Degrees F |
| Water Usage | 0.53 Gallons Per Rack |

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.