



METROMAX[®] PLATFORM ACCESSORIES

Stem Casters

- Promotes easy cleaning. Casters allow shelving units to be moved easily for access to floors and walls.
- Efficient Transport: Create a cart to efficiently move supplies throughout a facility or campus.



5PCX

5PCBX

Rigid stem casters are often ordered two per unit for improved tracking and handling. Rigid caster channel is provided with each two rigid stem casters at no charge.



5MPX

Polymer Stem Casters

- Corrosion resistant performance: all-polymer horn, stainless steel axle and hardware, 5" (127mm) diameter polyurethane wheel, sleeve-style axle bearing, and an optional toe-operated brake mechanism.
- Models available with antimicrobial product protection built into the tread.
- Load rating of 300 lbs. (135kg) and a temperature range from -20° to 120° F (-29° to 49° C) [continuous].
- Bumpers included.

| Model No. | Model No. Antimicrobial. | Wheel Diameter (in.) (mm) | Face (in.) (mm) | Load Rating (lbs.) (kg) | Type | Temperature Range (Continuous Usage) (Fahrenheit) (Celsius) | Approx. Pkd. Wt. (lbs.) (kg) |
|-----------|--------------------------|---------------------------|-----------------|-------------------------|-------------|---|------------------------------|
| 5PCX | 5PCXM | 5 127 | 1 1/4 32 | 300 135 | Stem/Swivel | -20°-120° -29°-49° | 2 0.9 |
| 5PCBX | 5PCBXM | 5 127 | 1 1/4 32 | 300 135 | Stem/Brake | -20°-120° -29°-49° | 2 0.9 |
| 5PCRX | — | 5 127 | 1 1/4 32 | 300 135 | Stem/Rigid* | -20°-120° -29°-49° | 2 0.9 |

*Note 1: Rigid casters are held in place by a connecting channel. When ordering, shelf width **must** be provided. Rigid connecting channel (aluminum) for 5PCRX caster: Model No. P18RC, P21RC, P24RC.

Note 2: Not suitable for cart wash and autoclave applications.

Standard Stem Casters

- Plated caster horns and hardware. Bumper included with each caster.
- Swivel, Swivel with Brakes, and Rigid Caster options available.

| Model No. | Wheel Diameter (in.) (mm) | Face (in.) (mm) | Load Rating (lbs.) (kg) | Type | Wheel Tread | Temperature Range (Continuous Usage) (Fahrenheit) (Celsius) | Approx. Pkd. Wt. (lbs.) (kg) |
|-----------|---------------------------|-----------------|-------------------------|-------------|--------------------|---|------------------------------|
| 5MX | 5 127 | 1 1/4 32 | 200 90 | Stem/Swivel | Resilient, Flat | -30°-160° -34°-71° | 2 1/2 1.1 |
| 5MBX | 5 127 | 1 1/4 32 | 200 90 | Stem/Brake | Resilient, Flat | -30°-160° -34°-71° | 2 5/8 1.2 |
| 5MRX | 5 127 | 1 1/4 32 | 200 90 | Stem/Rigid* | Resilient, Flat | -30°-160° -34°-71° | 3 1/2 1.5 |
| 5MDXA | 5 127 | 1 1/4 32 | 250 113 | Stem/Swivel | High Modulus Donut | -40°-180° -40°-82° | 2 1/2 1.1 |
| 5MDBXA | 5 127 | 1 1/4 32 | 250 113 | Stem/Brake | High Modulus Donut | -40°-180° -40°-82° | 2 5/8 1.2 |
| 5MDRXA | 5 127 | 1 1/4 32 | 250 113 | Stem/Rigid* | High Modulus Donut | -40°-180° -40°-82° | 2 3/8 1.1 |
| 5MPX | 5 127 | 1 1/4 32 | 300 135 | Stem/Swivel | Polyurethane, Flat | -30°-180° -34°-82° | 2 1/8 0.9 |
| 5MPBX | 5 127 | 1 1/4 32 | 300 135 | Stem/Brake | Polyurethane, Flat | -30°-180° -34°-82° | 2 1/4 1 |
| 5MPRX | 5 127 | 1 1/4 32 | 300 135 | Stem/Rigid* | Polyurethane, Flat | -30°-180° -34°-82° | 2 0.9 |

*Note: Rigid casters are held in place by a connecting channel. When ordering, shelf width **must** be provided. Rigid connecting channel (stainless steel): Model No. 18RS, 21RS, or 24RS.

Stainless Steel Cart-Washable Stem Casters

- Stainless horn, axle, and stem with sealed bearings. Bumper included with each caster.



5MPXGSA

| Model No. | Wheel Diameter (in.) (mm) | Face (in.) (mm) | Load Rating (lbs.) (kg) | Type | Wheel Tread | Temperature Range (Continuous Usage) (Fahrenheit) (Celsius) | Approx. Pkd. Wt. (lbs.) (kg) |
|-----------|---------------------------|-----------------|-------------------------|-------------|--------------------|---|------------------------------|
| 5MPXGSA | 5 127 | 1 1/4 32 | 300 135 | Stem/Swivel | Polyurethane, Flat | -30°-180° -34°-82° | 2 1/8 0.9 |
| 5MPBXGSA | 5 127 | 1 1/4 32 | 300 135 | Stem/Brake | Polyurethane, Flat | -30°-180° -34°-82° | 2 1/4 1 |
| 5MPRXGSA | 5 127 | 1 1/4 32 | 300 135 | Stem/Rigid* | Polyurethane, Flat | -30°-180° -34°-82° | 2 0.9 |

*Note: Rigid casters are held in place by a connecting channel. When ordering, shelf width **must** be provided. Rigid connecting channel (stainless steel): Model No. 18RS, 21RS, or 24RS.

Replacement Bumper for MetroMax i[®] and MetroMax Q[®]

Model No. M9992DBX



Replacement Bumper

Truck Dolly Bases

For heavy duty mobile applications. Truck dollies are available in aluminum or stainless construction with corner bumpers or wrap-around bumpers. For more information, refer to Spec Sheet 11.37.



Truck Dolly Base

Mounting Bolt Kit

When ordering a dolly frame for use with MetroMax i or MetroMax Q, include mounting bolt kit **DMK-2X** on order. Order one mounting bolt kit per dolly.