



JP Series

Industrial Cold Water Pressure Washers

Gasoline — Portable — Direct Drive



JP-3504-3MMB

*Contractors love the powerful JP Series for its portable design and great cleaning ability.
It removes dirt, mud, mold and mildew effortlessly from almost any surface.*

PUMP

- Equipped with Mi-T-M Pressure Relief Start
- Forged brass manifold
- Thermal relief valve
- In-line water strainer

FRAME

- Powder coated steel frame
- 10-inch flat-free tires

UNIT INCLUDES

- Quick connect nozzles – 0°, 15° and 25°
- 50-foot x 3/4-inch non-marking hose
- Insulated trigger gun

LIMITED WARRANTIES

- 1 year Mi-T-M unloader
- 3 year Honda, Kohler and Mi-T-M engines
- 7 year AR and Mi-T-M pumps

CERTIFICATION

- Intertek Certified to UL-1776 – US only (Honda engine models)



JP Series

Cold Water – Gasoline – Portable – Direct Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	UNLOADER	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JP-2403-3MHB	2400	2.4	196cc Honda GX200 OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	100 lb.	75 lb.
JP-2703-3MHB	2700	2.4	196cc Honda GX200 OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-2703-3MKB	2700	2.4	208cc Kohler CH270 OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-2703-3MMB	2700	2.4	212cc Mi-T-M OHV	Mi-T-M	Mi-T-M, adjustable pressure	36in.	37x21x24.5in.	110 lb.	85 lb.
JP-3003-3MHB	3000	3.0	270cc Honda GX270 OHV ⁺	AR	Mi-T-M, adjustable pressure	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3003-3MKB	3000	3.0	277cc Kohler CH395 OHV	AR	Mi-T-M, adjustable pressure	36in.	40x22.5x24.5in.	180 lb.	130 lb.
JP-3504-3MHB	3500	3.5	389cc Honda GX390 OHV ⁺	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-3504-3MKB	3500	3.5	429cc Kohler CH440 OHV	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-3504-3MMB	3500	3.5	420cc Mi-T-M OHV	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.
JP-4004-3MHB	4000	3.5	389cc Honda GX390 OHV ⁺	AR	Mi-T-M, adjustable pressure	48in.	40x22.5x24.5in.	192 lb.	142 lb.

⁺49 state fuel tank. Not for sale in California.

ACCESSORIES AND OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODEL
851-0338	50-foot x ¾-inch non-marking hose – For when you need extra hose for added mobility	All models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 0° spray with 25° coverage	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	2400 to 3000-PSI models
CX-0083	External bypass system – Allows more water into the system to protect from heat build-up	JP-2403 & JP-2703 models
CX-0084	External bypass system – Allows more water into the system to protect from heat build-up	JP-3504 & JP-4004 models