

Refrigerated Self-Service Multi-Purpose Island - Low/Med. Temp

MODELS SHOWN: MI44RF

Lengths include end panels
 52-1/4"L x 45-3/4"D x 40-5/8"H
 75"L x 45-3/4"D x 40-5/8"H

- MI44RF
- MI46RF



RAW MEAT (38°F)



PRODUCE/DELI (40°F)



FROZEN (0°F)

STANDARD FEATURES

- Breeze w/EnergyWise s/c refrigeration
- 1" bumper, double strip (specify color)
- Adjustable wire rack deck
- Casters
- Compressor air intake in one side & out other side. All louvered panels cannot be blocked
- Corrosion resistant stainless steel tub & fan shroud
- Integrated average product temperature adjustable from 0°F to 40°F. Low temp for frozen (excluding ice cream) (0°F), Medium temp for raw meat (38°F), Medium temp for produce/deli (40°F)
- NOTE: Maximum load height is 8-1/4" up from deck
- NOTE: Upper trim matches exterior color
- One year parts & labor; 5 year compressor warranty
- Removable deck pans provide complete access to evaporator coil & refrigeration connections
- Straight insulated glass ends

Features	Standard	Options
EXTERIOR COLOR	<input type="checkbox"/> Laminated (non-premium) Confirm pattern/grain direction	<input type="checkbox"/> Laminated (premium) Confirm pattern/grain direction <input type="checkbox"/> Painted (stock colors, specify RAL#) <input type="checkbox"/> Stainless steel (includes lower base)
INTERIOR COLOR	<input type="checkbox"/> Black	<input type="checkbox"/> Stainless steel
TRIM COLOR	<input type="checkbox"/> Black	<input type="checkbox"/> Stainless steel
BASE	<input type="checkbox"/> Black	<input type="checkbox"/> Stainless steel (w/stainless ext. only)
ELECTRICAL CONNECT	<input type="checkbox"/> 6' Straight blade power cord (self-cont.)	<input type="checkbox"/> 6' Locking power cord (self-cont.)
EVAPORATOR COIL	<input type="checkbox"/> Non-coated evaporator coil	<input type="checkbox"/> E-Coated evaporator coil
THERMOMETER	<input type="checkbox"/> Digital fahrenheit thermometer	<input type="checkbox"/> Digital celsius thermometer
MISCELLANEOUS		<input type="checkbox"/> Second year parts & labor warranty (excludes compressor)

Oasis®

Product Specifications

Intended Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.		
Zone	Intended Product To Be Displayed	Warmest Avg Prod Temp ° F
1	Packaged frozen (0°) Packaged raw meat (38°) Packaged produce/deli (40°)	0-38-40

Model Technical Specifications																
Model	L"	L1"	L2"	System Circuit Volts			Phs	Freq	Amps ***	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt
MI44RF	N/A	52.25	.00	Self-Contained	Circuit #1	208-240	1	60	15.90	2,326	2+G	6-20P or L6-20P	N/A	N/A	N/A	900
MI46RF	N/A	75.00	.00	Self-Contained	Circuit #1	208-240	1	60	15.69	2,418	2+G	6-20P or L6-20P	N/A	N/A	N/A	1,150
MI48RF	N/A	97.75	.00	Self-Contained	Circuit #1	208-240	1	60	18.13	2,524	2+G	6-30P or L6-30P	N/A	N/A	N/A	N/A

*** Does not include electric defrost on freezer models.

Important Notes:

1) Compressor air intake from rear and out front panel at toe kick. Front panel cannot be blocked.

⚠ WARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Regulatory Approvals:

All Models	Accordance with AHRI Std 1200 ETL Listed to UL 471 ETL Listed to CAN/CSA 22.2 No. 120 ETL Sanitation to NSF 7
------------	--



In Accordance with
AHRI Std 1200

DOE 2017
Energy Efficiency
Compliant