



# DUAL-TEMPERATURE WINE DISPENSER

PRO-LINE™ WINE E-SERIES™ 36" - 4 KEG

- Designed by wine-industry experts for performance and value
- Two dedicated temperature zones for optimal wine dispensing
- Pre-drilled for customer tower choice
- Commercial grade construction - built to last



**MDD36SW-E**

Stainless Steel



**MDD36W-E**

Black

**Shown:** Wine Font MTM-4PSS-W and  
Drip Tray DP-1020. Order Separately.



**Dual-Temperature:** Built In Digital Thermostats



Listed by Edison Testing Laboratories.  
Conforms to UL & NSF Standards.



Wine Certified

[www.micromatic.com](http://www.micromatic.com) • 1 (866) 327-4159

PRO-LINE™ WINE E-SERIES™ 36" - 4 KEG

Job Number: \_\_\_\_\_ Location: \_\_\_\_\_

| Part No.                           | Exterior        | Doors | Shipping Weight |
|------------------------------------|-----------------|-------|-----------------|
| <input type="checkbox"/> MDD36W-E  | Black           | 1     | 78 kg<br>172 lb |
| <input type="checkbox"/> MDD36SW-E | Stainless Steel | 1     | 78 kg<br>172 lb |

## Operating Performance

|                                 |                                    |              |            |
|---------------------------------|------------------------------------|--------------|------------|
| Capacity of 20 Liter Kegs       | 4 (2 per zone)                     | Running Amps | 3.6        |
| Cubic Feet (liters)             | TBD                                | Condenser HP | 1/6        |
| Hole for Wine Font              | 1                                  | Voltage      | 115/60/1   |
| Hole Diameter                   | 3"                                 | Plug Type    | NEMA-5-15P |
| Color-coded Digital Thermostats | 2 (Blue LED-Whites & Red LED-Reds) | Cord Length  | 8'         |
| Temperature Range - Whites      | 42-48° F (5.5 - 8.8C)              | Refrigerant  | R-134a     |
| Temperature Tange - Reds        | 55-65° F (12.7 - 18.3C)            | Charge oz    | 6.35       |
| Approval                        | ETL Listed, Energy Star            |              |            |

|             |   |
|-------------|---|
| Exterior    | 18 gauge stainless steel top, 22 gauge solid doors, 24 gauge steel front, sides and back  |
| Interior    | 20 gauge stainless steel floor and walls  |
| Ventilation | Front ventilated  |
| Plumbing    | Automatic condensate evaporator, no drain connection required. Evaporator condensate has been plumbed to a condensate pan located in the compressor housing |
| Insulation  | Foamed-in-place using high density, CFC-free polyurethane; 2" top, walls and floor  |
| Accessories | Castors or 6" fixed legs  |

## Dimensions

