



## Noble Warewashing LT-DT51 Select Low-Temperature Door-Type Dishwasher - 120V, 1 Phase

#495LTD51

Item #: 495LTD51 Qty: \_\_\_\_\_

Project: \_\_\_\_\_

Approval: \_\_\_\_\_ Date: \_\_\_\_\_



### Features

- Simple top-mounted digital display and control panel
- 17" pillarless opening provides easy loading and unloading
- 4-sided door design saves energy by retaining heat
- Designed for straight-through or corner operation
- Recirculating design uses less water and energy than fill-and-dump models

### Certifications



Hardwired



3/4" Water Connection



Field Convertible (Electrical)



NSF Listed



Energy Star Qualified



UL Certified

### Technical Data

Width	28 1/2 Inches
Depth	32 1/16 Inches
Dishwasher Height	Standard
Height (Closed)	62 15/16 Inches
Height (Open)	82 1/16 Inches
Amps	17.1 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	120 Volts
Application	Dishwashers


Technical Data	
Dishwasher Style	Straight / Corner
Features	Adjustable Height Auto Fill Built-In Drain Pump Digital Display Energy Star Qualified Field-Convertible (Electrical) NSF Listed
High or Low Temp	Low Temp
Number of Cycles	1 Cycle
Plug Type	Hardwire
Racks Per Hour	51
Type	Single Rack
Wash Cycle Time	60 - 360 Seconds
Wash Tank Capacity	4 gal.
Water Inlet Size	3/4 Inches
Water Temperature	120 - 140 Degrees F
Water Usage	0.86 Gallons Per Rack

## Notes & Details

Get spotless dishes every time with this Noble Warewashing low-temperature dishwasher. This dishwasher sanitizes with chemicals to effectively clean your glassware and dishes. It uses only 0.86 gallons of water per rack with a standard cycle that can be extended. Thanks to its integrated chemical pump, it can clean up to 51 racks per hour. This dishwasher's recirculating wash tank uses less water and energy than traditional fill-and-dump models.

This dishwasher is easy to use with a top-mounted digital display and simple control panel. It includes integrated wash and rinse arms with both tri-arm and single arm designs for greater coverage. This unit also has an automatic pumped drain to remove wash and rinse water at the end of each cycle. Its delime cycle eliminates hard water deposits that can cause damage to this dishwasher, making it easy to maintain and keep clean.

The dishwasher's 4-sided door saves energy by retaining heat. Its 17" pillarless opening ensures easy loading and unloading and can accommodate a single sheet pan. This unit ships for straight-through operation but can be converted to corner operation in the field. It has adjustable legs for use at your desired height. Its motor comes with thermal overload protection for safe use. This dishwasher requires a 120V, 1 phase electrical connection for operation, but it is field convertible to a 3-phase unit.

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).