



Noble Warewashing LT-UC24 Select Low-Temperature Undercounter Dishwasher - 120V, 1 Phase

#495LTUC24

Item #: 495LTUC24 Qty: _____

Project: _____

Approval: _____ Date: _____



Features

- Simple top-mounted digital display and control panel
- Washes up to 24 racks per hour using only 0.84 gallons of water per rack
- 14 7/16" door opening accommodates tall glassware
- Double-wall, labyrinth-style door prevents water, steam, and heat from escaping
- Recirculating design uses less water and energy than fill-and-dump models

Certifications

 Hardwired
  3/4" Water Connection
  NSF Listed

 UL Listed, US & Canada
  Energy Star Qualified

Technical Data

Width	22 11/16 Inches
Depth	24 Inches
Height	32 5/16 Inches
Amps	17.5 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	120 Volts
High or Low Temp	Low Temp
Horsepower	1 hp
Material	Stainless Steel

Technical Data	
Features	Auto Fill Built-In Drain Pump Chemical Pumps Energy Star Qualified NSF Listed
Number of Wash Cycles	1 Wash Cycle
Plug Type	Hardwire
Racks Per Hour	24
Style	Rack
Type	Undercounter Dishwashers
Wash Cycle Time	120 Seconds
Wash Tank Capacity	5.3 gal.
Water Inlet Size	3/4 Inches
Water Temperature	120 - 140 Degrees F
Water Usage	0.84 Gallons Per Rack

Notes & Details

Get spotless dishes every time with this Noble Warewashing low-temperature dishwasher. This dishwasher sanitizes with chemicals to effectively clean your glassware and dishes. It washes up to 24 racks per hour using only 0.84 gallons of water per rack. Each cycle begins with a soft start and fills automatically. It also allows cycles to be extended by 6 minutes. This unit's recirculating wash system uses less water and energy than traditional fill-and-dump models.

This dishwasher emits only 63 decibels for quiet, non-disruptive operation. It is easy to use with a top-mounted digital display and simple control panel. It includes integrated wash and rinse arms for comprehensive coverage. This unit also features an automatic pumped drain to remove wash and rinse water at the end of each cycle. Its delime notification and cycle simplifies maintenance.

The dishwasher includes built-in chemical pumps, and it enables a slow ramp up of water pressure. It has a 14 7/16" door opening for easy loading and unloading and to accommodate tall glassware. Its double-wall, labyrinth-style door prevents water, steam, and heat from escaping. This dishwasher requires a 120V, 1 phase electrical connection for operation.

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.