



Justrite Safety Group

413 - BLADE RUNNER™ W/DYNA-SHIELD®


PRODUCT INFORMATION BROCHURE





For over 70 years, the name Notrax® has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax® offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- **Track record of manufacturing high quality mats for over seventy years**
- **All products are manufactured in ISO certified facilities**
- **Notrax® offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries**




413 - BLADE RUNNER™ W/DYNA-SHIELD® is an anti-fatigue mat that is designed to provide traction with its wide ribs that run down the mat allowing for sure footing and is easy to sweep clean. The NoTrax® exclusive Dyna-Shield® PVC sponge is manufactured with a tough protective top layer that provides long lasting wear and outperforms in tear resistance and tensile strength. Designed for use in medium duty dry work areas.

Material: PVC

Features and Benefits:

- Wide ribs that run down the mat
- PVC foam provides added cushioning comfort
- Exclusive Dyna-Shield® top surface manufactured directly into the mat for long lasting wear.
- Superior tear resistance and tensile strength
- Beveled edges on all 4 sides of all stock, cuts and rolls
- Max length available up to 120 linear feet (minimum 2 rolls , available in increments of 2)
- Tolerances available upon request



MODEL: 413

SPECIFICATIONS

APPLICATIONS

- Dry Workstations
- Assembly Lines
- Packaging Areas
- Service Counters

Stock Sizes	2'x3', 2'x6', 3'x4', 3'x5', 3'x6', 3'x12'
Roll Sizes	2'x60', 3'x60', 4'x60'
Thickness	1/2"
Cut Lengths	2', 3', and 4' widths (up to 60' long)
Colors	<div>  Black  Black/Yellow </div>

Performance:

	Good	Better	Best	Superior
Wear Resistance	<div></div>	<div></div>	<div></div>	<div></div>
Anti-fatigue Performance	<div></div>	<div></div>	<div></div>	<div></div>
Slip Resistance	<div></div>	<div></div>	<div></div>	<div></div>



Anti-Fatigue



Cut Lengths



Insulation



TESTING DATA

Test	Test Description	Results
ASTM D-3574	Compression Deflection (@50%)	Thickness: 0.668 Compressed Load: 6.4 lbs./in 2
ATSM D3884-01	Abrasion Resistance (Measured in weight loss)	@500 cycles: .87 Grams (2.7%) @5000 cycles: 8.8 Grams (26.9%)
ASTM C-1028	Static Coefficient of Friction	Dry: 0.68 Wet: 0.50
ASTM D-1004-94a-03	Tear Resistance(Measured in lbs.)	20.1 lbs.
ASTM D-412	Elongation (Avg.)	Elongation: 28%

*Testing performed by an independent test laboratory.

NOTRAX®

5655 West 73rd Street
Chicago, IL 60638

PHONE: (800) 621-2802

FAX: (800) 322-7105

EMAIL: saleschicago@checkers-safety.com

www.notrax.com



A PRODUCT OF:



Justrite Safety Group is the leading source of safety equipment for flammables and hazardous materials storage and handling, asset protection, environmental protection spill containment, absorbents, specialized chemical storage, cable management, safety showers and eye/face washes, matting, and vehicle safety equipment. Learn more at Justrite.com, Checkers-safety.com, and Notrax.com.