

Project: _____

Item: _____

Quantity: _____

Pot & Pan Rack



PM2448



P2448

The environmentally friendly way to dry pots and pans. The unique T-Bar shelf design of these racks provides maximum air circulation, with the versatility to hold smaller products and heavy loads.

Mobile units are equipped with four 5" stem type swivel casters with brakes. Non-marking wheels prevent scuff marks and roll smoothly... even on tile floors.

- Constructed of primary extruded aluminum.
- Uprights are extruded aluminum pipe (6063-T5 alloy) with an outside diameter of 1 $\frac{5}{16}$ " and a wall thickness of .150; Marked in two-inch increments and fitted with plastic caps in each end.
- T-Bar shelves incorporates a rectangular frame of 1 $\frac{1}{2}$ " x 1 $\frac{3}{4}$ " x .070 wall extruded aluminum tube with 1 $\frac{1}{4}$ " x 2 $\frac{1}{4}$ " x .100 T-Bar welded inside, perpendicular to the shelf length. Each shelf corner has a heavy-duty extruded aluminum collar which accommodates the post. A stainless steel set screw is provided in each collar to lock the shelf at the desired height.
- Load capacity for each shelf is 900#. Recommended load capacity for mobile units is 1200# gross cart weight.
- **Five-Year Guarantee** against material defects and workmanship.
- **Lifetime Guarantee** against rust and corrosion.

► Pot & Pan Rack

Model No.	Size D-H-L	Number Of Tiers	Ship Lbs.
Stationary Units			
P2448	24" x 76" x 48"	4	59
P2460	24" x 76" x 60"	4	86
Mobile Units - 5" stem type swivel casters with brake			
PM2448	24" x 74" x 48"	4	68
PM2460	24" x 74" x 60"	4	97

All units shipped knocked down.



New Age Industrial Corp., Inc. || NewAgeIndustrial.com || Made in the USA

PO Box 520 • 16788 US Hwy 36 • Norton, Kansas 67654 || Phone: (800) 255-0104 • (785) 877-5121 || Fax: (877)-877-7687 • (785) 877-2616

This information is for general sales and engineering use only. New Age Industrial reserves the right to modify or make changes at any time, without notice, to materials and specifications.