

**REGENCY**  
Tables and Sinks

**Regency 24" x 17 1/2" Hand Sink with Waterloo Wall Mount  
Hands-Free Sensor 6 3/16" Gooseneck Spout Faucet**

#600FHSMK1824



**Technical Data**

Length	24 Inches
Width	17 1/2 Inches
Height	37 1/2 Inches
Spout Length	6 3/16 Inches
Bowl Depth	8 Inches
Backsplash Height	3 1/2 Inches
Faucet Height	11 1/16 Inches
Backsplash	With Backsplash
Basket Drain Size	3 1/2 Inches
Battery Type	AA

**Features**

- Rugged 16 gauge type 304 stainless steel
- 8" deep bowl with 1 1/2" IPS drain connection
- Solid chrome-plated brass faucet with 6 3/16" gooseneck spout
- Infrared proximity sensor with 30 second timeout
- Included 3 1/2" drain basket prevents clogs

**Certifications**



1-15P



3/8" Water Connection



CSA, US and Canada

Technical Data

Bowl Front to Back	14 Inches
Bowl Left to Right	24 Inches
Drain Outlet Size	1 1/2 Inches
Faucet Centers	Single
Features	Electronic Faucet Hands Free
Flow Rate	2.2 GPM
Gauge	16 Gauge
Included	Faucet
Installation Type	Wall Mounted
Material	Stainless Steel
Number of Compartments	1 Compartment
Number of Drainboards	None
Number of Faucets	1 Faucets
Plug Type	NEMA 1-15P
Power Type	AC Adapter Battery
Spout Type	Gooseneck
Stainless Steel Type	Type 304
Type	Hand Sinks
Water Inlet Size	3/8 Inches


Notes & Details

Maintain a sanitary environment in your restaurant, stadium, or manufacturing facility with this Regency single-hole multi-station hand sink with Waterloo faucet! Made of rugged 16 gauge type 304 stainless steel, this sink is rust- and corrosion-resistant. It's extremely durable and built for everyday commercial use. This sink helps to maintain cleanliness in your business and prevent the spread of germs, keeping your employees healthy.

The spacious 8" deep sink bowl is designed to accommodate vigorous handwashing with minimal water escaping the unit. Its legs are made of stainless steel, and they feature bullet feet that offer 1" of adjustability for convenience. A 3 1/2" high backsplash protects your walls from splashing and water damage. Plus, the included 3 1/2" drain basket keeps your drain clog-free. This unit comes with a 1 1/2" IPS drain connection. For safety, the outer edge of the sink bowl is curled under to eliminate any sharp edges.

The faucet of this unit has an infrared proximity sensor with a 30 second timeout feature and an adjustable sensor range of 1"-8". Because a sensor activates the water flow, it has several advantages over a traditional handle-style faucet. It is hands-free, which reduces the opportunity for germs to length, and it also prevents the faucet from running when it's not needed, which helps to cut down on your water bill.

The AC adapter with a level VI efficiency rating provides power for the faucet's control module, which installs below the countertop and connects to the faucet with an elbow and a 30" flexible supply line. Or, you can also use (4) AA batteries if an outlet isn't convenient, and to provide backup power in case of an outage. A mixing valve also allows you to easily set the output temperature to the desired level. This prevents burned hands from water that is too hot, while still ensuring that the water is warm enough for users to effectively wash their hands. A pair of 18" flexible stainless steel connectors with 1/2" NPSM female x 3/8" female compression fittings connect the mixing valve to your building's water lines.

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).