



Regency 18" x 17 1/2" Hand Sink with Waterloo Wall Mount
Hands-Free Sensor 6 3/16" Gooseneck Spout Faucet

#60FHSMK1818



Technical Data

| | |
|-------------------|-----------------|
| Length | 18 Inches |
| Width | 17 1/2 Inches |
| Height | 37 1/2 Inches |
| Spout Length | 6 3/16 Inches |
| Bowl Depth | 8 Inches |
| Backsplash Height | 3 1/2 Inches |
| Faucet Height | 11 1/16 Inches |
| Backsplash | With Backsplash |
| Basket Drain Size | 3 1/2 Inches |
| Battery Type | AA |

Features

- Rugged 16 gauge type 304 stainless steel
- 8" deep bowl with 1 1/2" IPS drain connection
- Solid chrome-plated brass faucet with 6 3/16" gooseneck spout
- Infrared proximity sensor with 30 second timeout
- Included 3 1/2" drain basket prevents clogs

Certifications



1-15P



3/8" Water Connection



CSA, US and Canada

Technical Data

| | |
|------------------------|--|
| Bowl Front to Back | 14 Inches |
| Bowl Left to Right | 18 Inches |
| Drain Outlet Size | 1 1/2 Inches |
| Faucet Centers | Single |
| Features | Electronic Faucet Faucet Included Hands Free |
| Flow Rate | 2.2 GPM |
| Gauge | 16 Gauge |
| Included | Faucet |
| Installation Type | Wall Mounted |
| Material | Stainless Steel |
| Number of Compartments | 1 Compartment |
| Number of Drainboards | None |
| Number of Faucets | 1 Faucets |
| Plug Type | NEMA 1-15P |
| Power Type | AC Adapter Battery |
| Spout Type | Gooseneck |
| Stainless Steel Type | Type 304 |
| Type | Hand Sinks |
| Water Inlet Size | 3/8 Inches |


Notes & Details

Maintain a sanitary environment in your restaurant, stadium, or manufacturing facility with this Regency single-hole multi-station hand sink with Waterloo faucet! Made of rugged 16 gauge type 304 stainless steel, this sink is rust- and corrosion-resistant. It's extremely durable and built for everyday commercial use. This sink helps to maintain cleanliness in your business and prevent the spread of germs, keeping your employees healthy.

The spacious 8" deep sink bowl is designed to accommodate vigorous handwashing with minimal water escaping the unit. Its legs are made of stainless steel, and they feature bullet feet that offer 1" of adjustability for convenience. A 3 1/2" high backsplash protects your walls from splashing and water damage. Plus, the included 3 1/2" drain basket keeps your drain clog-free. This unit comes with a 1 1/2" IPS drain connection. For safety, the outer edge of the sink bowl is curled under to eliminate any sharp edges.

The faucet of this unit has an infrared proximity sensor with a 30 second timeout feature and an adjustable sensor range of 1"-8". Because a sensor activates the water flow, it has several advantages over a traditional handle-style faucet. It is hands-free, which reduces the opportunity for germs to length, and it also prevents the faucet from running when it's not needed, which helps to cut down on your water bill.

The AC adapter with a level VI efficiency rating provides power for the faucet's control module, which installs below the countertop and connects to the faucet with an elbow and a 30" flexible supply line. Or, you can also use (4) AA batteries if an outlet isn't convenient, and to provide backup power in case of an outage. A mixing valve also allows you to easily set the output temperature to the desired level. This prevents burned hands from water that is too hot, while still ensuring that the water is warm enough for users to effectively wash their hands. A pair of 18" flexible stainless steel connectors with 1/2" NPSM female x 3/8" female compression fittings connect the mixing valve to your building's water lines.

 **WARNING:** This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.