



## TECHNICAL DATA

ROPC-006

# RUST-OLEUM® PROFESSIONAL CLEANERS LOW FOAM FLOOR CLEANER

## DESCRIPTION AND USES

Rust-Oleum® Professional Cleaners Low Foam Floor Cleaner is a professional strength formula designed for use in manufacturing facilities, warehouses, garages, waste management facilities and other heavy-duty environments. This concentrated, low foaming formula can be applied manually or used with commercial floor scrubbers. Formulated to remove the toughest grease and soils from industrial flooring, this fresh, lemon scented cleaner will not leave behind any residue. Safe for use on most coated and uncoated floor surfaces, including concrete, ceramic tile, quarry tile, stainless steel and more.

## PRODUCTS

| SKU    | DESCRIPTION   |
|--------|---------------|
| 382263 | 1 gal. Bottle |
| 388966 | 5 gal. Pail   |
| 388967 | 55 gal. Drum  |
| 388627 | 275 gal. Tote |

## DILUTION RATIOS

Lightly Soiled Floors: 1:128 (1 oz. of Cleaner to 1 gallon of water)

Heavily Soiled Floors: 1:64 (1 oz. of Cleaner to 64 oz. of water or 2 oz. of Cleaner to 1 gallon of water)

## PRODUCT FEATURES

- Removes The Toughest Grease And Oils
- Safe For Use On Concrete, Ceramic Tile, Quarry Tile, Stainless Steel And More
- Does Not Leave A Residue
- For Use With Commercial Floor Scrubbers Or Applied Manually
- Fresh Crisp Lemon Scent

## PRODUCT APPLICATION

### DIRECTIONS

1. Clean area by sweeping or vacuuming.
2. Apply diluted concentrate with an automatic scrubber or power washing tool.
3. For best results, thoroughly mop and rinse floor with water as well as changing mopping solution frequently. No rinsing required except on rubber or asphalt tile.

**NOTE:** Test in an inconspicuous area before use.

### PREVENTION

Wash hands thoroughly after handling.

## PHYSICAL PROPERTIES

|                    | LOW FOAM FLOOR CLEANER              |
|--------------------|-------------------------------------|
| Clarity            | Yellow                              |
| Odor               | Lemon scent                         |
| pH                 | 10.80-11.50                         |
| VOC                | 0.25% by weight                     |
|                    |                                     |
| Safety Information | For additional information, see SDS |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, Illinois 60061

Phone: 800-466-7126  
[www.rustoleum.com](http://www.rustoleum.com)

Form: RAK-56  
Rev.: 011525