FOOD PRESERVATION AND SOUS-VID

sammic

VACUUM PACKING MACHINE SE-208 120/50-60/1

Tabletop model. 8 m³/h. 280 mm.



P/N. 1141081

√ Safety system with protection against vacuum failure.

√ NSF-listed model.

NCLUDES

- √ Sensor Controls
- √ Up to 10 seconds of extra vacuum pull
- √ Soft air function
- √ Dry oil cycle

- √ BUSCH pump
- √ NSF Approved
- √ Clear methacrylate lid
- √ Filling plate

Accessories

☐ Vacuum packing bags

☐ External vacuum kit for Vac-Norm, containers and

SALES DESCRIPTION

280 mm. sealing bar. 8 m³/h Busch vacuum pump. Vacuum controlled by sensor.

- √ Powered by Busch.
- √ Vacuum controlled by sensor.
- √ Vacuum PLUS.
- √ Digital keyboard.
- Control panel equipped with display indicating the exact vacuum percentage.
- √ "Pause" button to marinate food.
- √ Safe liquid packing thanks to sensor control.
- √ Double seal.
- √ Cordless sealing bar.
- √ Bag-sealing programme.
- ✓ Pulse-controlled decompression.
- √ Vac-Norm ready with Automatic decompression.
- √ Stainless steel body and chamber. Deep-drawn chamber.
- ✓ Damped transparent lid of highly durable polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- √ Working hours counter for oil changes.











usa@sammic.com 1225 Hartrey Avenue 60202-1056 Evanston, IL phone +1 (224) 307-2232 toll free +1 844 275 3848



Project	Date
Item	Qty

Approved

FOOD PRESERVATION AND SOUS-VID

sammic

VACUUM PACKING MACHINE SE-208 120/50-60/1

Tabletop model. 8 m³/h. 280 mm.

SPECIFICATIONS

Pump capacity: 240 cf/h Bar length: 11 "

Total loading: 0.6 Hp

Vacuum pressure (maximum): 2 mbar Electrical supply: 120 V / 60 Hz / 1 \sim (6.3 A)

Internal dimensions

✓ Width: 11.3 "✓ Depth: 13 "✓ Height: 4.3 "

External dimensions (WxDxH)


✓ Width: 13.2 "✓ Depth: 16.9 "✓ Height: 13 "


Net weight: 71 lbs.


Noise level (1m.): 75 dB(A) Background noise: 32 dB(A)

Crated dimensions

15.7 x 20.7 x 15.4 " Gross weight: 77.2 lbs.









usa@sammic.com 1225 Hartrey Avenue 60202-1056 Evanston, IL phone +1 (224) 307-2232 toll free +1 844 275 3848



Project	Date
Item	Qty

Approved