



3-Person Hands-Free Floor Mount Stainless Steel Wash Station

Model	Flow-Rate
56F1	Standard 2.0 GPM
56F1-0.5	Low-Flow 0.5 GPM

Product Specifications

Constructed from welded #16 gauge type 304 stainless steel. The front, bottom and back are formed from a single sheet with a rolled rim on front and sides. Exposed surfaces have a blended uniform satin finish. Specially designed foot valves provide easy access to working parts without disconnecting mount or plumbing.

Outside Dimensions	60" x 20" x 45" High
Inside Bowl Size	57" x 16-1/2" x 8" Deep
Back Splash Height	10"
Water Activation	Single Foot Pedal Valve
Flow Rate	2 GPM
Inlet Connections	3/8" Male Compression
Drain Opening	2"
Finish	Satin
Strainer	1-1/2" Dia. Duo Basket Strainer

Includes

- (1) Floor mount wash station
- (1) Leg assembly set
- (4) Washers and nuts for connection sink to leg assembly set
- (3) Single foot pedal valve (bottom mount) with 4 nuts
- (3) Swivel gooseneck spout with aerator
- (3) Connecting tube for valve to spout connection
- (6) Fittings, brass, 0.375" male compression and 0.375" male NPT
- (3) Mixing check valve
- (1) Strainer assembly with basket

Product Compliance

NSF/ANSI 2 Food Equipment
NSF/ANSI 372 Low-Lead



Part: _____ Quantity: _____

Project: _____

Contact: _____

Date: _____

Approval: _____

Notes:



WARNING: Equipment that include faucets on this page may contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

COLUMBIA PRODUCTS
800.626.2117 • columbiasinks.com • info@columbiasinks.com

Top

60" (1524mm)

30" (762mm)

30" (762mm)

2" (51mm)

10.25" (267 mm)

16.5" (407mm)

20" (508mm)

5" R (12.7mm)

2" drain hole

1.5" (38mm)

57" (1448mm)

1.5" (38mm)

■ Front

The front view diagram shows the following dimensions:

- Top surface thickness: 10" (254mm)
- Distance from top surface to first horizontal support rail: 8" (203mm)
- Radius of the bottom-left corner: .5" R (12.7mm)
- Height from the floor to the bottom rail: 27" (686mm)
- Total width: 49.625" (1260.5mm)

Side view diagram of the sink and faucet assembly. Dimensions include:

- 20" (508mm) - Overall width of the faucet assembly.
- 2" (51mm) - Distance from the faucet handle to the spout.
- 7.5" (191mm) - Distance from the faucet handle to the spout.
- 1.5" (38mm) - Distance from the faucet handle to the spout.
- 35" (889mm) - Suggested floor to rim height.
- 9" (228.6mm) - Distance from the floor to the mounting holes.
- 9" (228.6mm) - Distance between mounting holes on center.
- 45° - Angle of the faucet handle.
- .75" (20mm) - Distance from the faucet handle to the spout.
- Supply Line to Spout - Label for the supply line.
- 2.875" (73.02mm) - Distance from the faucet handle to the spout.

[illegible]

Diagram illustrating the leg mounting holes for the table. The diagram shows a cross-section of the leg and the mounting holes. The leg thickness is 1.5". The mounting holes are 5/8" in diameter and spaced 9" on center. The distance from the edge of the leg to the first hole is 7 1/2".

A schematic diagram of the 375 inch compression device. The device is shown in profile, with a handle on the left and a spout on the right. A label '375" Compression' points to the main body of the device. Another label 'To Spout' points to the right side of the device. A dimension line indicates a distance of '7" (177mm) from Floor' from the floor to the bottom of the device. The entire diagram is enclosed in a circle.

Back Splash

3/8" Male Compression

Supply Line from Valve to Spout

