

# Howard-McCray

# **OD35E-48 SERIES – DAIRY OPEN MERCHANDISER** 48" MAXIMUM WIDTH - 78.5" HEIGHT STRAIGHT SIDES - ENDLESS DESIGN





MODEL NO.	DESCRIPTION	LENGTH	DEPTH	HEIGHT	VOLTAGE	AMPS	HP/BTUS	POWER CORD	WEIGHT
SC-OD35E-48-LED	Self Contained	48"	34.5"	78.5"	115/208-230	13.0	3/4	L14-20P	965
SC-OD35E-48-B-LED	Self Contained	48"	34.5"	78.5"	115/208-230	13.0	3/4	L14-20P	965
SC-OD35E-48-S-LED	Self Contained	48"	34.5"	78.5"	115/208-230	13.0	3/4	L14-20P	965

MODEL NUMBER PREFIX - SC = Self Contained R = Remote MODEL NUMBER SUFFIX - W = White B = Black S = Stainless Steel LED = LED lighting • Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

• Cases are equipped with drains; check your local building codes for connection requirements.

Specification subject to change without notice

COLORS ARE MÍXED AN ADĎITIONAL CHARGE WILL APPLY







A Division of HMC Enterprises LLC • 831 East Cayuga St • Philadelphia, PA 19124 USA

(215) 464-6800 • 1-800-344-8222 • Fax (215) 969-4890 • E-Mail: sales@howardmccray.com • www.howardmccray.com



# OD35E-48 SERIES – DAIRY OPEN MERCHANDISER 48" MAXIMUM WIDTH – 78.5" HEIGHT STRAIGHT SIDES – ENDLESS DESIGN

# STANDARD SPECIFICATIONS AND OPTIONAL FEATURES

### **CONSTRUCTION**

- UL Classified to ANSI/NSF 7
- Foamed in place CFC free foam
- Heavy gauge steel super structure
- Multi deck
- Endless design allows for continuous line up

### **INTERIOR**

- White, black, or stainless steel end panels
- Removable white, black, or stainless steel floor pans
- White, black, or stainless steel perforated rear wall (for even air distribution)
- Full length lighting at top of unit
- · 4 levels of lighted shelving
- 5 levels of product display
- · Stylish price tag molding on each shelf

#### **EXTERIOR**

- White, black, or stainless steel ends and front
- Removeable front grill allows for cleaning and servicing
- 1" bumper
- · Choice of end panels

### **FINISHES**

- · White, black, or stainless steel front rail
- · White, black, or stainless steel end trim
- Laminate, and custom paints available
- White, black, or stainless steel end panels
- White, black, or stainless steel rear panels

### **LIGHTING**

- 1 row at inside top of unit
- · 4 rows of lighted shelving

### **ELECTRICAL REQUIREMENTS**

- Self contained unit comes with cord and plug
- UL/CUL listed
- See Tech page for details on voltage

#### REFRIGERATION

- Low velocity fans located below deck area (to insure even flow of air)
- Electronic Control System with automatic air defrost to maintain balanced temperatures
- New high efficency air screen technology
- Self contained system
- Copeland hermetic unit
- · Remotes available

### **OPTIONAL FEATURES**

- Solid state lighting
- Night covers
- Security cover
- Peg bars
- Insulated divider for line ups
- Plexiglas divider for line ups
- Stainless steel, laminated or paint
- Product stops on shelving
- 4 different end panel choices
- · Digital thermometer

### **IMPORTANT NOTE:**

ALL REFRIGERATED CASES ARE DESIGNED TO OPERATE IN AN ENVIRONMENT OF 75 DEGREES AND 55% RELATIVE HUMIDITY.

PRODUCT MUST BE COOLED BEFORE BEING DISPLAYED WITHIN THE CASE. DRAIN IS REQUIRED





# **OD35E-48 SERIES – DAIRY OPEN MERCHANDISER** 48" MAXIMUM WIDTH - 78.5" HEIGHT STRAIGHT SIDES - ENDLESS DESIGN

## **TECHNICAL DATA**

Model No.		SC-OD35E-48-LED
Length with (2) ends		51"
Length without ends		48"
Height with ends		78.5"
Height without ends		78"
Depth with ends		34.5""
Depth without ends		34.25"
Endless design (Dimensions are +/- 1/4")		YES
Operating temperature		36°F to 40°F
Refrigerant (exp. valve)		Self-Contained
Compressor size HP		3/4
Defrost per day (24 hours)	Air Defrost	6 per day
Voltage		115/208-230
Amperage		13
Cord and plug		L14-20P
Exterior color		W, B, S
Interior color		W, B, S
# of rows / shelves		4 / 4
Shelf Size		(4) 18"
Shipping Info		
Height		86"
Depth		44"
Length		61"
Gross weight SC		965
Cubic feet		130

### (ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

Prefix Suffix SC = Self Contained B = Black R = Remote W = White

SS = Stainless Steel

LS = T8 lighting LED = LED lighting

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Cases are equipped with drains; check your local building codes for connection requirements.
- Specification subject to change without notice

**Howard** - McCray

A Division of HMC Enterprises LLC • 831 East Cayuga St • Philadelphia, PA 19124 USA



# OD35E-48 SERIES – DAIRY OPEN MERCHANDISER 48" MAXIMUM WIDTH – 78.5" HEIGHT STRAIGHT SIDES – ENDLESS DESIGN

# **DRAWINGS -SIDE VIEW - FRONT VIEW - FLOOR PLAN**

SIDE VIEW 4' FRONT VIEW 45.500 10.234 18.000 SHELF 18.000 10.000 63.250 10.000 18.000 **END** PANEL 3.000 78.000 78.000 10.000 18.000 REMOVABLE SPACER 10.000 24.688 30.969 23.000 12.000 14.938 13.349 14.750 8.000 (DRAIN) (ELECTRIC) 26.500 -5.000 3.000 -31.500 -34.500 4' FLOOR PLAN VIEW OD35E **SOLID SIDE STANDARD** 47.750 1.000 45.750 1.000 4.063 1.625 <del></del>

−6.313 78 9.125 + 19.188 ELECTRICAL CONNECTION REFRIGERATION CONNECTIONS -2.313 (REMOTE MODELS ONLY) 34.500 4.75 → 1" DRAIN CONNECTION - 24.75 34.5

**Howard-McCray** 

A Division of HMC Enterprises LLC • 831 East Cayuga St • Philadelphia, PA 19124 USA