



SV-200 • SV-250 Selectable Ice/Beverage Dispensers with Ice Crusher

SV-200 • SV-250 Selectable Ice/Beverage Dispensers
with Ice Crusher



Selectable SV-200 Ice/Beverage
Dispenser with S500 Ice Machine



Selectable SV-250 Ice/Beverage
Dispenser with Indigo Ice Machine



Featuring
icepic®



Servend's patented icepic™ feature is the industry's only built-in ice crusher providing a selection of crushed or cubed ice from a single ice maker/ice-beverage dispenser combination.

Standard Features

- Up to 10 beverage valves in a 30" wide ice/beverage dispenser.
- Increased beverage cooling efficiency vs. nugget-style ice.
- Long-lasting LED lighting illuminates the merchandiser while reducing energy usage and lifetime costs.
- Servend's patented Flex manifold makes carbonated or non-carbonated flavor changes possible in minutes. Great for seasonal promotions!
- 200 or 250 lbs. of ice storage.



ISO 9001:2000
Quality System
Certified

2100 Future Drive
Sellersburg, IN 47172 USA

Tel: 812.246.7000
Fax: 812.246.7024


www.manitowocbeverage.com/us



SV-200 • SV-250 Selectable Ice/Beverage Dispensers with Ice Crusher

Specifications

	SV-200	SV-250
Standard Features	LED lighted merchandiser, icepic graphics, key switch, leg kit, and drain kit.	
Approx. Shipping Weights	304 lbs. / 138 kgs.	335 lbs. / 152 kgs.
Approx. Countertop Weight (w/o ice)	235 lbs. / 107 kgs.	260 lbs. / 118 kgs.
Ice Storage Capacity	Up to 200 lbs. / 91 kgs.	Up to 250 lbs. / 114 kgs.
Electrical Requirements	Dispenser: 120V/60Hz/2.8FLA.	
Drain	Single 0.75" (1.91 cm) PVC (N.P.T.) drain fitting extends from drain pan. Units can be drained from the bottom or back of unit.	
Number of Valves	8 or 10	
Ice Machine Compatibility	Manual fill or top-mount with compatible ice machines. Contact MBE for adapter kit requirements for top-mounted ice machine applications.	
Manifold	8 valve 3-1-1-1-2 / 10 valve 3-1-2-1-3	
Options	Flomatic beverage valves. Both Flomatic 424 and 464 available in sanitary lever, push button, portion control, and autofill valve. Other valves available. Contact MBE for details. Other options: regulators, installation kits, and side splash panels, Americans with Disabilities Act (ADA) compliant selection touchpads.	



	SV-200	SV-250
Width	30.00"	30.00"
	76.20 cm	76.20 cm
Depth	31.13"	31.13"
	79.07 cm	79.07 cm
Height*	34.88"	40.88"
	88.60 cm	103.80 cm

*Height dimension without full lid.
Add 0.50" (1.27 cm) for full lid.