



DIRECT DRAW DISPENSER

PRO-LINE™ 17-1/2" - 2 1/6 KEGS

- Small kegerator footprint.
- Holds 2 - 1/6th kegs.
- Rugged keg slide - extends floor life.
- Commercial grade construction - built to last.
- Digital thermostat.



MDD17-E

Black



Listed by Edison Testing Laboratories.
Conforms to UL & NSF Standards.

www.micromatic.com • 1 (866) 327-4159

PRO-LINE™ 17-1/2" - 2 1/6 KEGS

Job Number: _____ Location: _____



| Part No. | Finish | Doors | Faucet | Shipping Weight |
|----------------------------------|--------|-------|--------|-----------------|
| <input type="checkbox"/> MDD17-E | Black | 1 | 1 | 63 kg |
| | | | | 138 lbs |

Operating Performance

| | | | |
|------------------------|------------|--------------|------------|
| Capacity of 1/6th Kegs | 2 | Running Amps | 1.5 |
| Cubic Feet (liters) | TBD | Voltage | 115/60/1 |
| Draft Tower | 1 | Plug Type | NEMA-5-15P |
| Faucet | 1 | Cord Length | 8' |
| Approval | ETL Listed | Refrigerant | R290 |
| Compressor HP | 1/10 | Charge oz | 2.8 |
| BTUs | 850 | Thermostat | Digital |

| | |
|-------------|---|
| Exterior | 18 gauge stainless steel top, 22 gauge solid doors, 24 gauge steel front, sides and back. Black Vinyl: Front, sides. |
| Interior | 20 gauge stainless steel floor, reinforced frame, 24 gauge galvanized walls |
| Ventilation | Back ventilated |
| Plumbing | Drain Tray: 3/4" NPT drain includes hose and drain bottle. Automatic condensate evaporator, no drain connection required. Evaporator condensate has been plumbed to a condensate pan located in the compressor housing. |
| Insulation | Foamed-in-place using high density, CFC-free polyurethane; 2" top, walls and floor. |
| Casters | Standard |

Dimensions

