Product Specification Sheet - CWDC1050

CWDC1050	3 Qt Die-Cast Aluminum Casserole Pan, 10 x 3"

Country of Origin	CN	Harmonized Tariff Code	7615.10.2025	UK Tariff Code	7615 10 10 90	Minimum Order Quantity	1 EA

Item Specifications

Individual Unit Overall Dimensions

Length	Width	Height
12.625 (in)	9.875 (in)	6.5 (in)
32 (cm)	25 (cm)	16.5 (cm)

Min. Temp.	-20 (°F)	-29 (°C)
Max Temp.	450 (°F)	232 (°C)

Piece Weight	2.712 (lbs)	1.230 (kg)
Unit Measure Net Weight	2.712 (lbs)	1.230 (kg)
Unit Measure Gross Weight	3.360 (lbs)	1.524 (kg)
Individual Unit Cube	0.3333 (ft^3)	0.00944 (m^3)
Capacity	3 (qt)	()

UPC Label on Product?	Yes
UPC Application	Label
BPA Free	Yes
NSF	No
Dishwasher Safe	No
Microwave Safe	No

Component	Material	ItemNumber	Material Detail	Origin	Gauge	Diameter	Weight
Casserole Pan	Aluminum (Die-Cast)		Black Coating	China		9.875 (in)	865 (g)
-Interior Coating	Non-Stick (Whitford Xylan Over Die Cast Aluminum)		Whitford Xylan 8253, Black Coating	China			
-Exterior Coating	High-Temp Metallic Ceramic Coating		Whitford Xylan 8294, Black Coating	China			
Lid w/ Knob	Combo: Stainless Steel (201) & Glass		Clear Glass & Mirror Finish on Lid & Knob	China	0.6 (mm)	9.875 (in)	365 (g)

Packaging and UPC Information

	Packaging	Quantity	Length	Width	Height	Weight	Cube	Plastic Waste	Paper Waste	UPC
Piece Packaging	3 Ply Corrugated Carton Hang Tag,Poly Bag	1 EA	10.125 (in) 25.7 (cm)	4.5 (in) 11.4 (cm)	10.75 (in) 27.3 (cm)	3.153 (lbs) 1.4 (kg)	0.28 (ft^3) 0.008 (m^3)			727875104137
Master Carton	5 Ply Corrugated Carton	6 EA	20.75 (in) 52.7 (cm)	11.5 (in) 29.2 (cm)	14.5 (in) 36.8 (cm)	20.16 (lbs) 9.1 (kg)	2 (ft^3) 0.057 (m^3)			30727875104138

Pallet Specifications

TI (cartons/layer)	7	HI (layers/pallet)	5	Total Cartons	35	Total Units	210	Pallet Height	63 (in)

Product Notes

* Diameter of Induction Ring: 6.625" * Dimensions of Pan, No Lid No Handles: 9.875 x 9.875 x 3" * Each Lid has a 6" Diameter Glass Window * Safe for use with open flame, ovens, hot-plates, and induction cookers.

Packaging Details

Handles and hardware are packaged in a sealed poly bag. Each lid is placed into a poly bag then into a bubble poly bag. Lids are placed inverted on top of each pan. The complete unit is then placed into a poly bag. Poly bags with an opening larger than 5"/12.70cm require two punched holes and a multilingual suffocation warning. A piece UPC label is applied to the poly bag of each unit. Each unit is then packaged in a 3-Ply white carton, a piece UPC label is applied to each carton. There are 6 each per master(5-Ply), two UPC labels are applied to each master carton. An instruction sheet is provided with each unit.



Tablecraft Products Company World Headquarters - 801 Lakeside Drive, Gurnee, IL 60031-2489 USA

Phone: +1 (847)855-9000 Fax: +1 (847)855-9012 www.tablecraft.com