

1-800-MAGLINE (624-5463)



HDL360F

INDICATOR LAMP

- Single-step mode: constant green
- Continuous step mode: flashes green

SINGLE-STEP/CONTINUOUS STEP BUTTON

- Depress once to change mode
- Depress longer (>3 sec.) to switch off

D DUAL SPEED CONTROL

SPECIFICATIONS			
	UNIVERSAL HDL360U	FOLD HDL360F	UNIVERSAL 4W HDL360U-4W
Capacity	725 lbs.	725 lbs.	725 lbs.
Maximum speed (steps per minute)	10	10	10
Weight (without battery)	75 lbs.	77 lbs.	88 lbs.
Maximum step height	8″	8″	8"
Overall height	64"	47" (folded) 70" (unfolded)	64"
Width	22"	22"	22"
Depth	19"	19"	19"
Battery capacity approximate steps (with maximum load)	120 steps	120 steps	120 steps
Battery capacity approximate steps (with half-load)	220 steps	220 steps	220 steps



STEP EDGE BRAKE SYSTEM GUARANTEES THE HIGHEST LEVEL OF SAFETY.

1 - 800 - MAGLINE (624-5463)

Options & Accessories

NOSES



 P/N
 W"
 D"
 WT.(LBS.)


 930030
 18.8
 9.4
 4.0

 930018
 14
 7
 2.25

 930003
 16.5
 13.4
 4.0

Grooved nose plate with beveled edge slides easily under loads. Not compatible with HD models.

ACCESSORIES



 P/N
 W"
 D"
 WT.(LBS.)

 930085
 17.7
 7.5
 4.0

 930084
 18.8
 9.4
 5.0

 Solid nose plate with beveled edge slides easily under loads. Not compatible with

easily under loads. Not compatible with HD models.

WHEELS



030245 10 2.75 10" 4-ply tubed pneumatic wheel with precision bearings. Not compatible with HD models.



10" non-marking microcellular, puncture-proof wheel with precision bearings. Not compatible with HD models.



Battery securing clip holds the battery firmly in place in high impact situations.



In-transit DC battery charger conveniently charges using the vehicle's lighter.



930156 165 2 1.25 Heavy duty containment straps hold product in place during transport.



Keg hook holds keg in place securely during delivery. Not compatible with HD models.

FASTER, SAFER DELIVERIES ON STAIRS











magliner.com

- Magline, Inc. 1205 West Cedar Street | Standish, MI 48658
 1.800.MAGLINE (624.5463) (989) 512.1000 (Outside U.S. & Canada)
- 🗢 Fax: (989) 803.5941