

Project:	AIA#
Item:	
Location:	SIS#
Approved:	

SCHOOL MILK COLD WALL COOLER

ST49HC Dual Access Cooler **Hydrocarbon Series**

MODEL: ST49HC-S

7 Year Parts/Labor Warranty 7 Year Compressor Warranty



CABINET CONSTRUCTION

- Stainless steel exterior and interior
- Stainless steel lids, hinged doors and door latches
- Dual sided access
- Full electronic control
- Heavy-duty epoxy coated steel wire floor racks standard
- Floor drain is centrally located for easy cleaning and connecting to drain hose with hose adapter
- Flexible compression door gaskets, ensures a tight seal
- · Self-latching doors/lids with safety bumpers
- Exterior thermometer
- Cylinder locks
- 4" Heavy-duty plate casters (2 with locks)
- Cold wall milk coolers are designed to hold product temperature during service. Product should be removed at the end of service and moved to long-term, refrigerated storage

OPTIONS & ACCESSORIES

- Corner bumpers
- · Cafeteria tray slides
- Graphics

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE &
- Maintains product temperature between 36°F-40°F










3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax: 1-336-245-6453 Beverage-Air.com Sales@bevair.com



MODEL	ST49HC-S	
EXTERNAL DIMENSIONAL DATA		
Width Overall	49"	
Depth Overall	31 ¼"	
Height Overall with Casters	41 1/8"	
Number of Lids/Doors	Dual Access	
Both Lids Extended	61"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	18.97	
Internal Width Overall (in)	46"	
Internal Depth Overall (in)	27"	
Internal Height Overall (in)	25 ½"	
CASE CAPACITY		
13" X 13" X 11"	12	
19" X 13" X 11"	8	
ELECTRICAL DATA		
Full Load Amperes	3.7	
REFRIGERATION DATA		
Horsepower	1/2	
Capacity (BTU/Hr)	1976	
Heat Rejection (BTU/Hr)	2964	
Charge (lbs/grams/ounces)	0.1656 / 75 / 2.65	
SHIPPING DATA		
Gross Weight - Crated	336 lbs	
Height - Crated	47"	
Width - Crated	52"	
Depth - Crated	34"	

We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM).

School Milk Cooler - Dual Access





ELECTRICAL CONNECTION



115/60/1 NEMA 5-15P Unit pre-wired at factory and include 8' long cord and plug set.

