



T755S

WIRED REMOTE SENSING THERMOSTAT



Exclusively For
Professionals



T755S

WIRED REMOTE SENSING THERMOSTAT



Model #	Commercial		7 Day Programmable		5/1/1 Programmable		Non-Programmable		Stages Of Heat	Stages Of Cool	Heat Pump Systems With Auxiliary	Conventional Systems	PTAC Mode	Display Size (square inches)	Filter Change Reminder	Room Temperature Calibration	Adjustable Heat & Cool Temperature Swing	Programmable Fan	Adjustable Setpoint Limits	Auto Changeover	Memory Type (permanent)	Outdoor Sensor Capable	Sensor Capable	WiFi Ready	Fan Speeds	Warranty (years)	Terminals
	C	7D	5/1/1	NP	C	3*	2*																				
T755S		7D	5/1/1	NP	C	3*	2*						7												3	5	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, S1, S2

Stages* = 2 Stages For Conventional Heat & Cool

Remote Sensing Options for the T755S Thermostat

The T755S can be configured in one of three ways with wired remote sensors to achieve maximum comfort in a home. These accessories are just another way PRO1 has improved comfort at a low cost to homeowners.

Outdoor remote Sensing

The R250S can be used as an outdoor temperature sensor to set a Dual Fuel Balance Point. This feature chooses the most efficient heat source based on the outside temperature. At this predetermined point the system will automatically choose the best heating source to save energy.

Slab Sensing

The R250S can also be used as a floor sensor in Radiant Heating applications. By sensing the temperature at the heat source, this accessory greatly improves the comfort of the space and the efficiency of the heating system.

Indoor Remote Sensing

The R251S provides a better level of comfort by averaging as many as 16 different sensing points. Additional indoor sensors increase the accuracy of the temperature reading throughout a home.



R251S

R250S

rev. 2024



1-800-PRO1-559 (776-1559)

PRO
www.pro1iaq.com