

Models

**TRUE MANUFACTURING CO., INC. PROJECT NAME** 2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Ітем # Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 MODEL # Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

LOCATION AIA # **Q**TY SIS #

TGM-DZ-48-SC/SC-B-W TGM-DZ-48-SC/SC-W-W TGM-DZ-48-SC/SC-S-W TGM-DZ-48-SC/SC-S-S

## **True Glass Merchandiser**

## Curved Glass, Solid Colored End Dual Zone



TGM-DZ-48-SC/SC-B-W



## TGM-DZ-48-SC/SC-W-W



## TGM-DZ-48-SC/SC-S-W



## TGM-DZ-48-SC/SC-S-S

# **FEATURES**

- True's dual zone glass merchandisers combine efficient, high volume merchandising and exceptional refrigeration with an elegant curved glass front for sophisticated presentation of high end desserts and pastries.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP).
- Refrigerated section features high capacity, factory balanced refrigeration system. Standard temperature range maintains cabinet temperatures of 33°F to 41°F (.5°C to 5°C), ideally suited for refrigerated bakery and cold deli products.
- Two (2) rear sliding glass doors for back access.
- Exterior powder coated FDA black rounded front and back, solid wood sides with aluminum cover and front panels. Color options available (upcharge may apply) - white or stainless.
- Interior powder coated FDA white over CRS material. Color options available (upcharge may apply) - black or stainless.
- Three (3) tiered levels of adjustable wire cantilever shelves that match cabinet interior color. Chrome plated wire shelves standard on stainless units.
- Curved glass front is single pane tempered glass with extra large viewing area to maximize product presentation.
- LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.

STANDARD OPTIONS		
Exterior Color	Black, White, or Stainless Steel	
Interior Color	Black, White, or Stainless Steel	
Shelving	White, Black, Chrome, or Mezzanine	

#### ROUGH-IN DATA Specifications subject to change without notice. Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number). Cabinet Dimensions **Crated Weight** Crated Weight Cord (inches) White/Black Model Stainless Model Length (mm) (lbs.) (lbs.) NEMA (total ft.) (kg) (kg) Model Doors Shelves \٨/ D н HP Voltage Amps Config. (total m) TGM-DZ-48-SC/SC-Δ-Δ 2 6 481/4 39 491/8 1⁄4 115/60/1 10.0 5-15P 8 TBD TBD 1226 990 1247 1⁄4 220-240V/50Hz 2.0 2.44 TBD TBD 1⁄4 220V/60Hz 2.3

Δ Represents Exterior/Interior (B-black, W-White, S-Stainless)

▲ Plug type varies by country

	APPROVALS:	AVAILABLE AT:
MADE WITH- IN THE USA		
03.24 Printed in U.S.A		

Models:

TGM-DZ-48-SC/SC-B-W TGM-DZ-48-SC/SC-W-W

TGM-DZ-48-SC/SC-S-W TGM-DZ-48-SC/SC-S-S

## STANDARD FEATURES

- DESIGN
- True's combination "refrigerated" and "dry" display case glass merchandiser combines efficient, high volume merchandising and exceptional refrigeration with an elegant curved glass front for sophisticated presentation of high end end deli, desserts and pastries
- Please note: If units are banked together, because of side panel, a 1/2" (13mm) gap will remain between units.

#### **REFRIGERATION SYSTEM**

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP).
- True's self-cleaning RCU technology eliminates the need to clean the condenser coil, reduces energy consumption and helps maintain the coldest temperatures and freshest product.
- High capacity, factory balanced refrigeration system that has two (2) temperature range options. Standard temperature range maintains cabinet temperatures of 33°F to 41°F (.5°C to 5°C), ideally suited for refrigerated bakery and cold deli products. Optional temperature range maintains cabinet temperatures of 42°F to 65°F (5.5°C to 18.3°C), ideally suited for chocolate & wine options.
- Pull Out Condensing unit slides out for easy cleaning and maintenance.

#### **CABINET CONSTRUCTION**

- Exterior powder coated FDA black rounded front and back, solid wood sides with aluminum cover and front panels. Color options available (upcharge may apply) - white or stainless. Interior - powder coated FDA white over CRS material. Color
- options available (upcharge may apply) black or stainless. Insulation - entire cabinet structure is foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential
- (GWP) Welded, heavy duty steel frame rail, black powder coated for corrosion protection
- Frame rail fitted with leg levelers.

#### CURVED FRONT DISPLAY GLASS

Curved glass front is single pane tempered glass with extra large viewing area to maximize product presentation.

#### **REAR DOORS**

- Two (2) rear sliding glass doors for back access.
- Each door fitted with 12" (305 mm) long aluminum handle. Sliding doors ride on stainless steel V-channel with stainless steel bearings. Doors fit within plastic channel frame.

#### SHELVING

Six (6) adjustable heavy duty PVC coated wire shelves standard. Each shelf supports a maximum weight of 150 lbs. (69 kg).

#### PAN CAPACITY

Cabinet holds four (4) 18"L x 26"D (458 mm x 661 mm) display pans, two (2) 9"L x 26"D (229 mm x 661 mm) display pans and six (8) 12"L x 18"D (305 mm x 458 mm) display pans. Pans supplied by others.

#### LIGHTING

LED interior lighting, two (2) clips underneath shelf to keep wires in place. Safety shielded.

### **MODEL FEATURES**

- Evaporator is epoxy coated to eliminate the potential of corrosion
- Pull out condensing unit slides out for easy cleaning and maintenance.
- Electronic temperature control.

115/60/1

NEMA-5-15R

NSF/ANSI Standard 7 compliant for open food product. Tested and certified for performance at NSF Type II: 80°F (27°C) and 55% relative humidity.

#### ELECTRICAL

Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.





## STANDARD OPTIONS

Upcharge and lead times may apply.

- Ľ Black exterior White exterior
- Stainless steel exterior
- White interior
- ā Black interior
- Stainless steel interior Solid Colored Exterior Sides with color matching interior (SC)
- White wire shelves
- Black wire shelves
- Chrome plated wire shelves
- Stainless steel mezzanine shelves

#### **OPTIONAL FEATURES/ACCESSORIES**

Upcharge and lead times may apply.

- 220-240V/50Hz
- 220V/60Hz
- Custom exterior colors (contact factory for details) Chocolate/Wine model available ā
- Glass shelves Frosted glass shelves
- Ratchet lock
- Electrical Receptacle
- Exterior top scale shelf
- Exterior small top service shelf
- Exterior medium top service shelf
- Exterior large top service shelf External front shelf kit (only available in black)
- External rear service shelf shelf kit (only available in black)
- 4" (102mm) Castors
- 21/2" (64mm) castors
- 6" (153mm) legs



48 9/32 [1226mm] METRIC DIMENSIONS ROUNDED UP TO MO Elevation Right Plan 3D Back THE NEAREST WHOLE MILLIMETER KCL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

#### **TRUE MANUFACTURING CO., INC.**

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 • Fax (636)272-2408 • Toll Free (800)325-6152 • Intl. Fax# (001)636-272-7546 • www.truemfg.com

## **True Glass Merchandiser:** Curved Glass, Solid Colored End Dual Zone

