

Cotterman®

ASSOCIATES
CLARK



3TR26A6E10B8C1P6

TILT'N'ROLL® Rolling Steel Ladders

THE TiltNRoll® features a special balanced design that allows it to tilt easily to the rolling position when pulled toward the user. The user is not required to extend a foot to assist in tilting the ladder to the rolling position. Once tilted, the ladder can be easily moved from job to job on the two 4" diameter wheels.

TiltNRoll® ladders are one-piece welded assemblies shipped ready-to-use. The ladders are supplied with handrails that extend 30" above the top step.

- Steel - 450 lb. load rating.
- 59° climb angle.
- Rests on four 2½" rubber pads.
- 7" deep, 24" wide steps with 10" deep top step.
- Gray powder coat is the standard finish.
- Arrives ready to use.
- TiltNRoll® ladders meet applicable OSHA and ANSI standards.
- Cal-OSHA models also available.

NO. OF STEPS	TOP STEP HEIGHT	OVERALL HEIGHT	WORKING HEIGHT (approx.)	BASE WIDTH	BASE LENGTH	SHIPPING WEIGHT LBS.	PERFORATED TREAD	SERRATED TREAD
							PART NUMBER	PART NUMBER
2 STEP	20"	50"	86"	28"	24"	43	2TR26A6E10B8C1P6	2TR26A3E10B8C1P6
3 STEP	30"	60"	96"	28"	31"	55	3TR26A6E10B8C1P6	3TR26A3E10B8C1P6
4 STEP	40"	70"	106"	28"	37"	66	4TR26A6E10B8C1P6	4TR26A3E10B8C1P6
5 STEP	50"	80"	116"	28"	43"	78	5TR26A6E10B8C1P6	5TR26A3E10B8C1P6



2TR26A3E10B8C1P6



3TR26A6E10B8C1P6



4TR26A6E10B8C1P6



5TR26A3E10B8C1P6



Available at CLARKINC.biz

© 2023 Material Control, Inc.