

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project :       |      |
|-----------------|------|
| Model #:        |      |
| Item #:         | Qty: |
| Available W/H : |      |
| Approval :      |      |

Model: TOM-50LB-SP(-A)-N NO PLUMBING REQUIRED

## Horizontal Open Display Cases

Low Profile Solid Side Panel

## Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



#### TOMD-LW

\* Top display dry case available (optional)

\* Image shown here is white case



## \_\_\_ FEATURES & BENEFITS =\_\_

### ■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

## ■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### ■ Modern design

By integrating great contours with durable structures, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics. Safety reinforced tempered glass front shield optimizes the merchandiser's display effects of fresh salads, sandwiches, desserts and beverages. Its elegant contemporary euro design will enhance any store application. Ideal for eye-catching displays and convenient access with fast service in high traffic areas.

#### Interior materials available in two standards

SP: stainless steel interior for sanitary purposes SP-A: black coated interior with mirrored sides for maximized display effects.

- Solid side panels used to ensure durability
- Standard back-guard improves airflow
- Perforated interior back wall & top for improved air flow
- Foamed with polyurethane, high-density cell insulation (CFC free)
- Front air intake and rear air discharge









| Model             | CU./FT. | # of<br>Shelves | НР  | AMPS | Crated<br>Weight (lbs.) | L x D x H<br>(inches) |
|-------------------|---------|-----------------|-----|------|-------------------------|-----------------------|
| TOM-50LB-SP(-A)-N | 9.8     | 1               | 3/4 | 6.9  | 505                     | 503/4 x 345/8 x 461/8 |

# Horizontal Open Display Cases

## Model: TOM-50LB-SP(-A)-N

| ELECTRICAL DATA                  |                       |  |  |  |
|----------------------------------|-----------------------|--|--|--|
| Voltage                          | 115/60/1              |  |  |  |
| Plug Type                        | (i) NEMA 5-15P        |  |  |  |
| Full Load Amperes                | 6.9                   |  |  |  |
| Compressor HP                    | 3/4                   |  |  |  |
| Refrigerant                      | R-290                 |  |  |  |
| DIMENSIONAL DATA                 |                       |  |  |  |
| Net Capacity (cu. ft.)           | 9.8                   |  |  |  |
| Ext. Dimension (L x D x H) (in.) | 503/4 x 345/8 x 461/8 |  |  |  |
| Int. Dimension (L x D x H) (in.) | 483/8 x 24 x 171/2    |  |  |  |
| Net Weight (lbs.)                | 376                   |  |  |  |
| Gross Weight (lbs.)              | 505                   |  |  |  |
| # of Shelves                     | 1                     |  |  |  |
| Shelf Size (in.)                 | 481/4 x 103/4         |  |  |  |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

WARRANTY: 2 Year Parts and Labor Warranty
Additional 3 Year Warranty on Compressor

#### **STANDARD FEATURES:**

- Anti-corrosion coated evaporator
- Simple plug-in installation
- Patented self-contained system, no plumbing required
- Solar powered digital thermometer
- Digital electronic thermostat with defrost control
- LED lighting interior
- Recommended operating conditions:


TOM models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product.

#### **OPTIONAL ACCESSORIES:**


- 4" caster. ½" diameter & 13 TPI: G8F6500101 (non-brake). G8F6500201 (w/ brake)
- Top display dry cases: TOMD-50LW(B) (Low), TOMD-50HW(B) (High)
- Night cover: NCT-50-W (White), NCT-50-B (Black)
  - Night cover option won't be able to apply on TOM-LW(B)/SW(B)-N models if TOMD-L/HW(B) dry case is already installed on top of the unit.
- Price tag channel: P5000000ZK (481/4"L)


## **PLAN VIEW**

(unit: inch)



**TOP VIEW** 





**FRONT VIEW** 

Ver.20171114



■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002









